

SJ3220/26 E

ELECTRIC SCISSORS



STANDARD FEATURES

- Drivable at full height
- Variable speed, dual front wheel electric drive
- AGM Batteries
- Dual holding brakes
- SKYCODED™ Colour coded and numbered wiring system
- On-board visual interface with diagnostic capabilities
- Shroud style, impact resistant composite control box with extended cable
- Low battery indicator light on control box
- Proportional controls for drive & lift functions
- 0.91 m Roll out extension deck
- 24V DC Power source
- Low voltage battery protection
- 25% Gradeability
- Solid rubber, non-marking tyres
- Pothole protection system
- Tilt alarm with drive & lift cut-out (3.5° x 1.5°)
- Flashing light
- 12.5 m/s Wind rating (SJ3220 E only)
- Lanyard attachment points
- Operator horn
- Forklift pockets and tie down / lift lugs
- Overload sensing system
- Fold down hinged railing system
- Half height spring hinged entry gate
- Universal smart charger
- Single point emergency lowering
- White noise alarm
- All motion audible alarm
- Telematics ready
- 2-Year Gold Leaf Warranty (5-year structural warranty)



- 16% operational carbon saving compared to previous model



- Up to 20% improvement in duty cycle



- ZERO emissions



- <70 dB inherently quiet machine operation (excl. alarms)
- White noise/broadband alarms - *optional*



- 90% recyclable (by weight)




- 60% less hydraulic connections – reduces leak potential
- ECOTRAY leak containment - *optional*
- Bio-degradeable hydraulic oil - *optional*



- Telematics – remote diagnostics reduces site visits (operational carbon footprint)

SJ3220/26 E ELECTRIC SCISSORS

Dimensions	SJ3220 E	SJ3226 E
A Work Height	7.95 m	9.79 m
B Raised Platform Height	5.95 m	7.79 m
C Lowered Platform Height	0.99 m	1.17 m
D Overall Width	0.82 m	0.82 m
E Overall Length	2.33 m	2.32 m
F Stowed Height (Rails Up)	2.10 m	2.29 m
G Stowed Height (Rails Down)	1.75 m	1.93 m
H Platform Width (Inside Dimension)	0.70 m	0.70 m
I Platform Length (Inside Dimension)	2.10 m	2.10 m
Specifications	SJ3220 E	SJ3226 E
Extension Deck (Roll Out)	0.91 m	0.91 m
Ground Clearance (Pothole Raised)	10 cm	10 cm
Ground Clearance (Pothole Deployed)	1 cm	1 cm
Wheelbase	1.75 m	1.75 m
Weight	1,776 kg	1,905 kg
Gradeability	25%	25%
Turning Radius (Inside)	1.09 m	1.09 m
Turning Radius (Outside)	2.64 m	2.64 m
Lift Time (With Rated Load)	34 sec	55 sec
Lower time (With Rated Load)	24 sec	30 sec
Drive Speed (Stowed)	3.4 km/h	3.4 km/h
Drive Speed (Raised)	0.9 km/h	0.9 km/h
Maximum Drive Height	Full Height	Full Height
Capacity (Overall)	408 kg	227 kg
Distributed Capacity (Main Platform)	272 kg	114 kg
Distributed Capacity (Extension Deck)	136 kg	113 kg
Local Floor Load (With Rated Load)	749 kPa	718 kPa
Overall Floor Load (With Rated Load)	11.9 kPa	107 kPa
Maximum # of persons at 0 m/s wind rating	2	2
Maximum # of persons up to 12.5 m/s wind rating	1	0 (Optional 1 up to 5.63 m)
Tyre Type	Solid, N/M	Solid, N/M
Tyre Size	16 x 5 x 12	16 x 5 x 12



ACCESSORYZERS ‡

- Light duty pipe rack
- Heavy duty pipe rack
- Board carrier
- Tool caddy
- ECOTRAY leak containment system (SJ3226 E only)
- Secondary Guarding Lift Enable (SGLE)
- Perimeter lights (Cannot be combined with dual flashing lights)

OPTIONS †

- Dual flashing lights
- (SJ3226 E only) 12.5 m/s Wind rating 1 up to 5.63 m
- Lead acid batteries
- Lockable swingout trays
- Full height spring hinged entry gate
- Bio oil
- ELEVATE telematics (1-year, 3-year or 5-year plans available)

† Standard lead times may be increased when optional equipment is added, consult factory.
‡ Capacities and machine weights may differ when accessories and options are added.

*Only available with ELEVATE telematics

Skyjack Australia Pty Ltd
Unit 1, 35 Honeycomb Drive
Eastern Creek
NSW 2766
Australia
Phone +61 (0) 2 9854 0700
Fax +61 (0) 2 9854 0777
Email: jcranmer@skyjack.com

www.skyjack.com

SKYJACK
simply reliable