

SJ4740 E

ELECTRIC SCISSORS



STANDARD FEATURES

- Drivable at full height
- Variable speed, dual rear wheel electric drive
- Dual holding brakes
- SKYCODED™ Colour coded and numbered wiring system
- On-board visual interface with diagnostic capabilities
- Shroud style, impact resistant composite control box with extended cable
- Low battery indicator light on control box
- Proportional controls for drive & lift functions
- 0.91 m Roll out extension deck
- 24V DC Power source
- Low voltage battery protection
- 25% Gradeability
- Solid rubber, non-marking tyres
- Pothole protection system
- Tilt alarm with drive & lift cut-out (3.5° x 1.5°)
- Flashing light
- Lanyard attachment points
- Operator horn
- Forklift pockets and tie down / lift lugs
- Overload sensing system
- Fold down hinged railing system
- Half height spring hinged entry gate
- Universal smart charger
- Single point emergency lowering
- Arm guard with slow close descend
- Telematics ready



- 16% operational carbon saving compared to previous model



- Up to 20% improvement in duty cycle



- ZERO emissions



- <70 dB inherently quiet machine operation (excl. alarms)
- White noise/broadband alarms - *optional*



- 90% recyclable (by weight)




- 60% less hydraulic connections – reduces leak potential
- ECOTRAY leak containment - *optional*
- Bio-degradable hydraulic oil - *optional*



- Telematics – remote diagnostics reduces site visits (operational carbon footprint)

SJ4740 E ELECTRIC SCISSORS

Dimensions	SJ4740 E
A Work Height	13.86 m
B Raised Platform Height	11.86 m
C Lowered Platform Height	1.41 m
D Overall Width	1.20 m
E Overall Length	2.41 m
F Stowed Height (Rails Up)	2.53 m
G Stowed Height (Rails Down)	2.03 m
H Platform Width (Inside Dimension)	1.07 m
I Platform Length (Inside Dimension)	2.19 m
Specifications	SJ4740 E
Extension Deck (Roll Out)	0.90 m
Ground Clearance (Pothole Raised)	11 cm
Ground Clearance (Pothole Deployed)	1 cm
Wheelbase	1.85 m
Weight	2,955 kg
Gradeability	25%
Turning Radius (Inside)	0.79 m
Turning Radius (Outside)	2.90 m
Lift Time (With Rated Load)	88 sec
Lower time (With Rated Load)	53 sec
Drive Speed (Stowed)	3.14 km/h
Drive Speed (Raised)	0.8 km/h
Maximum Drive Height	Full Height
Capacity (Overall)	350 kg
Distributed Capacity (Main Platform)	230 kg
Distributed Capacity (Extension Deck)	120 kg
Local Floor Load (With Rated Load)	956 kPa
Overall Floor Load (With Rated Load)	11.2 kPa
Maximum # of persons at 0 m/s wind rating	3
Maximum # of persons up to 12.5 m/s wind rating	0 (Optional 1 up to 7.32 m)
Tyre Type	Solid, N/M
Tyre Size	16 x 5 x 12



ACCESSORYZERS ‡

- Light duty pipe rack
- Heavy duty pipe rack
- Board carrier
- Tool caddy
- ECOTRAY leak containment system
- Secondary Guarding Lift Enable (SGLE)
- Perimeter lights (Cannot be combined with dual flashing lights)

OPTIONS †

- All motion audible alarm
- Dual flashing lights
- White noise alarm
- Wiring for AC outlet at platform
- 12.5 m/s Wind rating 1 up to 7.32 m
- 250 Ah Batteries
- AGM Batteries
- Lockable swingout trays
- Full height spring hinged entry gate
- Bio oil
- ELEVATE telematics (1-year, 3-year or 5-year plans available)
- ELEVATE Battery Management System (BMS)*

† Standard lead times may be increased when optional equipment is added, consult factory.

‡ Capacities and machine weights may differ when accessories and options are added.

*Only available with ELEVATE telematics

www.skyjack.com

Skyjack UK
Unit 1, Maes-y-Clawdd
Maesbury Road Industrial Estate
Oswestry, Shropshire, SY10 8NN
Tel: +44 1691 676235
Fax: +44 1691 676239
Email: info@skyjackeurope.co.uk

Skyjack SAS (France)
74 Rue Sibert
F-42400 Saint Chamond
France
Tel: +33 (0) 4 78 73 53 32
Fax: +33 (0) 4 78 56 52 42

Skyjack Hebebühnen GmbH
(Germany)
Därmanbusch 2a
D-58456 Witten
Tel: +49 (0) 2302 20 26 909
Fax: +49 (0) 2302 20 25 671

Skyjack AB (Sweden)
Agnesbergsvägen 28
424 38 Agnesberg
Sweden
Tel: +46 (0) 31 21 22 45
Fax: +46 (0) 31 787 65 10

SKYJACK
simply reliable