



FLUORESCENT TUBE CARRIER

Fluorescent lights are fragile and can break if not handled properly. The fluorescent tube carrier features a rubber padded base designed to provide a soft resting spot, and is equipped with a buckle strap to secure and safely carry the fluorescent lights to their work location.

Ideal for maintenance needs, the fluorescent tube carrier is mounted outside the platform to optimise work space and increase productivity.



Use only on listed models	VERTICAL MAST LIFTS				
Model Serial Number	Platform Capacity (including load on Tube Carrier)	Height	Rated load on Tube Carrier	Horizontal Load Rating (Manual Force)	Wind Rating
SJ12 A600 000 001+, 140 000 00+	227 kg 1 person	3.66 m	23 kg	200 N	12.5 m/s
SJ16* A600 000 001+, 140 000 00+	227 kg 1 person	3.66 m	23 kg	200 N	12.5 m/s
	227 kg 1 person	4.88 m	23 kg	200 N	0 m/s
SJ12 E A601000906 - A601999999	227 kg 1 person	3.66 m	23 kg	200 N	0 m/s
SJ16 E A601000906 - A601999999	227 kg 1 person	4.88 m	23 kg	200 N	0 m/s
SJ20 E A601000906 - A601999999	159 kg 1 person	5.94 m	23 kg	200 N	0 m/s

Overall tube carrier weight 7.7 kg
* With Wind Rating Option Only

Skyjack UK
Unit 1, Maes-y-Clawdd
Maesbury Road Industrial Estate
Oswestry, Shropshire, SY10 8NN
Tel: +44 1691 676235
Fax: +44 1691 676239
Email: info@skyjackeurope.co.uk

**Skyjack SAS
(France)**
74 Rue Sibert
F-42400 Saint Chamond
France
Tel: +33 (0) 4 78 73 53 32
Fax: +33 (0) 4 78 56 52 42

**Skyjack Hebebühnen GmbH
(Germany)**
Därmannbusch 2a
D-58456 Witten
Tel: +49 (0) 2302 20 26 909
Fax: +49 (0) 2302 20 25 671

**Skyjack AB
(Sweden)**
Agnesbergsvägen 28
424 38 Agnesberg
Sweden
Tel: +46 (0) 31 21 22 45
Fax: +46 (0) 31 787 65 10

SKYJACK
simply reliable
www.skyjack.com/en-eu/accessoryzers