

# NORTH AMERICA

LIST PRICING (USD)  
EFFECTIVE JANUARY 1ST, 2025



# VERTICAL MAST LIFTS

LIST PRICING (USD) EFFECTIVE JANUARY 1ST, 2025

## SJ12 E ..... \$22,230

- 12' (3.65 m) Raised platform height
- 500 lbs (227 kg) Capacity
- 30.5" (0.78 m) Overall width
- 54" (1.37 m) Overall length
- 78" (1.97 m) Stowed height
- 26.5" x 37" (0.67 x 0.94 m) Platform size (inside)

## SJ16 E ..... \$24,335

- 15'7" (4.75 m) Raised platform height
- 500 lbs (227 kg) Capacity
- 30.5" (0.78 m) Overall width
- 54" (1.37 m) Overall length
- 78" (1.97 m) Stowed height
- 26.5" x 37" (0.67 x 0.94 m) Platform size (inside)

### Standard Features

- Overload sensing system
- Drivable at full height with platform retracted
- Variable speed, front two wheel electric drive
- 90° Steering (zero inside turning radius)
- Dual holding brakes
- On-board visual interface with diagnostic capabilities
- Shroud style, impact resistant composite control box
- Proportional controls for drive & lift functions
- 16" (0.41 m) Traversing platform
- Multistage lift cylinders
- 24V DC power source
- 2 x 12V batteries
- Low voltage battery protection
- 25% Gradeability
- Solid rubber, non-marking tires
- Fixed pothole protection system
- 110V AC outlet at platform with GFI
- 28 mph (12.5 m/s) wind rating (SJ12 E only)
- Tilt sensor (2.5° x 1.5°)
- Tilt alarm with drive & lift cut-out
- All motion audible alarm
- Lanyard attachment points
- Operator horn
- Lift rings/tie downs
- Half height spring hinged entry gate
- Removable oil filter
- Telematics ready
- 2 Year Gold Leaf Warranty (5 year structural warranty)

### Options<sup>‡</sup>

Dual flashing lights .....	\$645
4 x 6V batteries.....	\$340
AGM batteries .....	\$1,495
Saloon gate .....	\$490
ECOTRAY leak containment system .....	\$850
Bio oil.....	\$535
28mph (12.5 m/s) wind rating kit to 12ft (SJ16 E only).....	\$1,140
Secondary guarding lift enable (SGLE) .....	\$180
Non destructive testing .....	\$1,595
White noise alarm .....	\$345
Perimeter lights.....	\$945

<sup>‡</sup> Standard lead times may be increased when optional equipment is added, consult factory

\*\* Capacities, and machine weights may differ when options are added



# VERTICAL MAST LIFTS

LIST PRICING (USD) EFFECTIVE JANUARY 1ST, 2025

**SJ20 E ..... \$30,230**

- 19'6" (5.94 m) Raised platform height
- 350 lbs (159 kg) Capacity
- 31.5" (0.80 m) Overall width
- 54" (1.37 m) Overall length
- 79" (2.00 m) Stowed height
- 26.5" x 37" (0.67 x 0.94 m) Platform size (inside)

**Standard Features**

- Overload sensing system
- Drivable at full height with platform retracted
- Variable speed, front two wheel electric drive
- 90° Steering (zero inside turning radius)
- Dual holding brakes
- On-board visual interface with diagnostic capabilities
- Shroud style, impact resistant composite control box
- Proportional controls for drive & lift functions
- 16" (0.41 m) Traversing platform
- Multistage lift cylinders
- 24V DC power source
- 2 x 12V batteries
- Low voltage battery protection
- 25% Gradeability
- Solid rubber, non-marking tires
- Fixed pothole protection system
- 110V AC outlet at platform with GFI
- Tilt sensor (2.5° x 1.5°)
- Tilt alarm with drive & lift cut-out
- All motion audible alarm
- Lanyard attachment points
- Operator horn
- Lift rings/tie downs
- Half height spring hinged entry gate
- Removable oil filter
- Telematics ready
- 2 Year Gold Leaf Warranty (5 year structural warranty)

**Options<sup>‡</sup>**

Dual flashing lights .....	<b>\$645</b>
4 x 6V batteries.....	<b>\$340</b>
AGM batteries .....	<b>\$1,495</b>
Saloon gate .....	<b>\$490</b>
ECOTRAY leak containment system .....	<b>\$850</b>
Bio oil.....	<b>\$535</b>
28mph (12.5 m/s) wind rating kit to 12ft (SJ16 E only).....	<b>\$1,140</b>
Secondary guarding lift enable (SGLE) .....	<b>\$180</b>
Non destructive testing .....	<b>\$1,595</b>
White noise alarm .....	<b>\$345</b>
Perimeter lights.....	<b>\$945</b>

<sup>‡</sup> Standard lead times may be increased when optional equipment is added, consult factory

<sup>\*\*</sup> Capacities, and machine weights may differ when options are added



This literature is for illustrative purposes only. Consult Operating Maintenance and Parts Manual for proper procedures. Work platforms have been tested to comply with ANSI and CSA standards as interpreted by Skyjack Inc. Prices and specifications are subject to change without notice.

# DC ELECTRIC SCISSOR LIFTS

LIST PRICING (USD) EFFECTIVE JANUARY 1ST, 2025

## SJ3213 micro ..... \$22,560

- 13' (3.96 m) Raised platform height (indoor)
- 500 lbs (272 kg) Capacity
- 32" (0.81 m) Overall width
- 60" (1.5 m) Overall length
- 75.8" (1.9 m) Stowed height (rails up)
- 27.5" x 60" (0.7 x 1.5 m) Platform size (outside)

## SJ3219 micro ..... \$23,855

- 18' 1" (5.5 m) Raised platform height (indoor)
- 500 lbs (227 kg) Capacity
- 32" (0.81 m) Overall width
- 60" (1.5 m) Overall length
- 79.5" (2.0 m) Stowed height (rails up)
- 27.5" x 60" (0.7 x 1.5 m) Platform size (outside)

### Standard Features

- Drivable at full height
- Variable speed, dual front wheel electric drive
- Dual holding brakes
- SKYCODED™ Color coded and numbered wiring system
- On-board visual interface with diagnostic capabilities
- Shroud style, impact resistant composite control box with extended cable
- 28 mph (12.5 m/s) Wind rating (12' on SJ3213 micro, 16' on SJ3219 micro)
- Low battery indicator light on control box
- Proportional controls for drive & lift functions
- 20" (0.5 m) Roll out extension deck
- 24V DC Power source
- 110V AC Outlet on platform with GFI
- 2 x 12V Batteries
- Low voltage battery protection
- 25% Gradeability
- Solid rubber, non-marking tires
- Fixed pothole protection system
- Tilt alarm with drive & lift cut-out (3° x 1.5°)
- All motion audible alarm
- Lanyard attachment points
- Operator horn
- Forklift pockets and tie down / lift lugs
- Overload sensing system
- Solid rails
- Full height spring hinged entry gate
- Telematics ready
- 2-Year Gold Leaf Warranty (5-year structural warranty)

### Options<sup>‡</sup>

Dual flashing lights .....	\$645
AGM Batteries .....	\$1,495
Lockable swingout trays .....	\$125
ECOTRAY leak containment system .....	\$850
Secondary guarding lift enable (SGLE) .....	\$180
Non destructive testing .....	\$1,595
White noise alarm .....	\$345
Perimeter Lights.....	\$945
Xstep .....	\$2,455

<sup>‡</sup> Standard lead times may be increased when optional equipment is added, consult factory

\*\* Capacities, and machine weights may differ when options are added



# DC ELECTRIC SCISSOR LIFTS

LIST PRICING (USD) EFFECTIVE JANUARY 1ST, 2025

**SJ3215 E ..... \$22,560**

- 14' 7" (4.44 m) Raised platform height
- 600 lbs (272 kg) Capacity
- 32" (0.81 m) Overall width
- 71" (1.80 m) Overall length
- 66" (1.67 m) Stowed height (rails down)
- 25" x 61" (0.64 x 1.54 m) Platform size (inside)

**SJ3219 E ..... \$23,855**

- 18' 6" (5.64 m) Raised platform height
- 500 lbs (227 kg) Capacity
- 32" (0.81 m) Overall width
- 71" (1.80 m) Overall length
- 79.60" (2.01 m) Stowed height (rails down)
- 25" x 61" (0.64 x 1.54 m) Platform size (inside)

**Standard Features**

- Drivable at full height
- Variable speed, dual front wheel electric drive
- 90° steering (zero inside turning radius)
- Dual holding brakes
- SKYCODED™ color coded and numbered wiring system
- On-board visual interface with diagnostic capabilities
- Shroud style, impact resistant composite control box with extended cable
- Proportional controls for drive & lift functions
- 3' (0.91 m) Roll out extension deck
- 24V DC power source
- 110V AC Outlet on platform with GFI
- Low voltage battery protection
- 25% Gradeability
- Solid rubber, non-marking tires
- Pothole protection system
- 28 mph (12.5 m/s) wind rating
- Tilt sensor (3.5° x 1.5°)
- Tilt alarm with drive & lift cut-out
- All motion audible alarm
- Lanyard attachment points
- Operator horn
- Forklift pockets and tie down/lift lugs
- Overload sensing system
- RAPIDFOLD hinged railing system (SJ3219 E only)
- Half height spring hinged entry gate
- Telematics ready
- 2 Year Gold Leaf Warranty (5 year structural warranty)

**Options\***

Flashing light.....	\$345
Dual flashing lights .....	\$645
110V AC Outlet on platform with GFI .....	\$275
250 Ah batteries.....	\$440
AGM Batteries.....	\$1,495
Lockable swingout trays.....	\$125
EE rating package .....	\$1,400
<small>(Cannot be combined with telematics keypad, 250 Ah or AGM batteries, single or dual flashing lights, AC power on platform, perimeter lights, white noise alarm or ECOTRAY)</small>	
Full height spring hinged entry gate.....	\$370
ECOTRAY leak containment system .....	\$850
Bio oil.....	\$275
Secondary guarding lift enable (SGLE) .....	\$180
Non destructive testing .....	\$1,595
White noise alarm .....	\$345
Perimeter lights.....	\$945
Xstep .....	\$2,455

\* Standard lead times may be increased when optional equipment is added, consult factory

\*\* Capacities, and machine weights may differ when options are added



This literature is for illustrative purposes only. Consult Operating Maintenance and Parts Manual for proper procedures. Work platforms have been tested to comply with ANSI and CSA standards as interpreted by Skyjack Inc. Prices and specifications are subject to change without notice.

# DC ELECTRIC SCISSOR LIFTS

LIST PRICING (USD) EFFECTIVE JANUARY 1ST, 2025

## SJ3220 E..... \$28,130

- 19' 6" (5.95 m) Raised platform height
- 900 lbs (408 kg) Capacity
- 32" (0.81 m) Overall width
- 91.6" (2.32 m) Overall length
- 69" (1.75 m) Stowed height (rails down)
- 28" x 83" (0.71 x 2.11 m) Platform size (inside)

## SJ3226 E..... \$33,125

- 25' 7" (7.79 m) Raised platform height
- 500 lbs (227 kg) Capacity
- 32" (0.81 m) Overall width
- 91.6" (2.32 m) Overall length
- 76" (1.93 m) Stowed height (rails down)
- 28" x 83" (0.71 x 2.11 m) Platform size (inside)

### Standard Features

- Drivable at full height
- Variable speed, dual rear wheel electric drive
- Dual holding brakes
- SKYCODED™ color coded and numbered wiring system
- On-board visual interface with diagnostic capabilities
- Shroud style, impact resistant composite control box with extended cable
- Proportional controls for drive & lift functions
- 3' (0.91 m) Roll out extension deck
- 24V DC power source
- 110V AC Outlet on platform with GFI
- Low voltage battery protection
- 25% Gradeability
- Solid rubber, non-marking tires
- Pothole protection system
- 28 mph (12.5 m/s) wind rating (SJ3226 E up to 18' 6" (5.63 m))
- Tilt sensor (3.5° x 1.5°)
- Tilt alarm with drive & lift cut-out
- All motion audible alarm
- Lanyard attachment points
- Operator horn
- Forklift pockets and tie down/lift lugs
- Overload sensing system
- Fold down hinged railing system
- Half height spring hinged entry gate
- Telematics ready
- 2 Year Gold Leaf Warranty (5 year structural warranty)

### Options†

Flashing light.....	\$345
Dual flashing lights .....	\$645
6' (1.83 m) Powered ext. deck (SJ3220)* .....	\$5,950
<small>*adds 387 lbs (176 kg) to unit weight and reduces overall capacity to 800 lbs (363 kg)</small>	
250 Ah batteries.....	\$440
AGM Batteries.....	\$1,495
Lockable swingout trays.....	\$125
EE rating package (not available with telematics access keypad) .....	\$1,400
<small>(Cannot be combined with telematics keypad, 250 Ah or AGM batteries, single or dual flashing lights, AC power on platform, perimeter lights, white noise alarm or ECOTRAY)</small>	
Full height spring hinged entry gate.....	\$370
ECOTRAY leak containment system (not available on SJ3220).....	\$860
Bio oil.....	\$660
Secondary guarding lift enable (SGLE) .....	\$180
Non destructive testing .....	\$1,595
White noise alarm .....	\$345
Perimeter lights.....	\$945

† Standard lead times may be increased when optional equipment is added, consult factory

\*\* Capacities, and machine weights may differ when options are added



# DC ELECTRIC SCISSOR LIFTS

LIST PRICING (USD) EFFECTIVE JANUARY 1ST, 2025

**SJ4726 E..... \$35,295**

- 25' 8" (7.82 m) Raised platform height
- 1,000 lbs (454 kg) Capacity
- 47" (1.19 m) Overall width
- 91.6" (2.32 m) Overall length
- 75" (1.90 m) Stowed height (rails down)
- 42" x 83" (1.07 x 2.11 m) Platform size (inside)

**SJ4732 E..... \$42,490**

- 31' 8" (9.65 m) Raised platform height
- 700 lbs (318 kg) Capacity
- 47" (1.19 m) Overall width
- 91.6" (2.32 m) Overall length
- 78.5" (1.99 m) Stowed height (rails down)
- 42" x 83" (1.07 x 2.11 m) Platform size (inside)

**Standard Features**

- Drivable at full height
- Variable speed, dual rear wheel electric drive
- Dual holding brakes
- SKYCODED™ color coded and numbered wiring system
- On-board visual interface with diagnostic capabilities
- Shroud style, impact resistant composite control box with extended cable
- Proportional controls for drive & lift functions
- 4' (1.22 m) Roll out extension deck
- 24V DC power source
- 110V AC Outlet on platform with GFI
- Low voltage battery protection
- 25% gradeability
- Solid rubber, non-marking tires
- Pothole protection system
- 28 mph (12.5 m/s) wind rating
- Tilt sensor (3.5° x 1.5°)
- Tilt alarm with drive & lift cut-out
- All motion audible alarm
- Lanyard attachment points
- Operator horn
- Forklift pockets and tie down/lift lugs
- Overload sensing system
- Fold down hinged railing system
- Half height spring hinged entry gate
- Telematics ready
- 2 Year Gold Leaf Warranty (5 year structural warranty)

**Options†**

Flashing light.....	<b>\$345</b>
Dual flashing lights .....	<b>\$645</b>
250 Ah batteries.....	<b>\$440</b>
AGM Batteries.....	<b>\$1,495</b>
Lockable swingout trays .....	<b>\$125</b>
EE rating package (not available with telematics access keypad) .....	<b>\$1,400</b>
<small>(Cannot be combined with telematics keypad, 250 Ah or AGM batteries, single or dual flashing lights, AC power on platform, perimeter lights, white noise alarm or ECOTRAY)</small>	
Full height spring hinged entry gate.....	<b>\$370</b>
ECOTRAY leak containment system .....	<b>\$860</b>
Bio oil.....	<b>\$660</b>
Secondary guarding lift enable (SGLE) .....	<b>\$180</b>
Non destructive testing .....	<b>\$1,595</b>
White noise alarm .....	<b>\$345</b>
Perimeter lights.....	<b>\$945</b>

† Standard lead times may be increased when optional equipment is added, consult factory  
 \*\* Capacities, and machine weights may differ when options are added



# DC ELECTRIC SCISSOR LIFTS

LIST PRICING (USD) EFFECTIVE JANUARY 1ST, 2025

**SJ4740 E..... \$57,055**

- 38' 11" (11.86 m) Raised platform height
- 770 lbs (349 kg) Capacity
- 47" (1.19 m) Overall width
- 95.2" (2.41 m) Overall length
- 79.8" (2.03 m) Stowed height (rails down)
- 42" x 86" (1.06 x 2.19 m) Platform size (inside)

## Standard Features

- Drivable at full height
- Variable speed, dual rear wheel electric drive
- Dual holding brakes
- SKYCODED™ color coded and numbered wiring system
- On-board visual interface with diagnostic capabilities
- Shroud style, impact resistant composite control box with extended cable
- Proportional controls for drive & lift functions
- 3' (0.91 m) Roll out extension deck
- 24V DC power source
- 110V AC Outlet on platform with GFI
- Low voltage battery protection
- 25% Gradeability
- Solid rubber, non-marking tires
- Pothole protection system
- 28 mph (12.5 m/s) wind rating (Up to 24' (7.3 m))
- Tilt sensor (3.5° x 1.5°)
- Tilt alarm with drive & lift cut-out
- All motion audible alarm
- Lanyard attachment points
- Operator horn
- Forklift pockets and tie down/lift lugs
- Overload sensing system
- Fold down hinged railing system
- Half height spring hinged entry gate
- Telematics ready
- 2 Year Gold Leaf Warranty (5 year structural warranty)

## Options†

Flashing light.....	<b>\$345</b>
Dual flashing lights .....	<b>\$645</b>
AGM Batteries .....	<b>\$2,250</b>
Lockable swingout trays .....	<b>\$125</b>
Full height spring hinged entry gate.....	<b>\$370</b>
ECOTRAY leak containment system .....	<b>\$860</b>
Bio oil.....	<b>\$730</b>
Secondary guarding lift enable (SGLE) .....	<b>\$180</b>
Non destructive testing .....	<b>\$1,595</b>
White noise alarm .....	<b>\$345</b>
Perimeter lights.....	<b>\$945</b>
28 mph (12.5 m/s) Wind rating to 18' 6" (SJ3226 E only) .....	<b>\$525</b>

† Standard lead times may be increased when optional equipment is added, consult factory

\*\* Capacities, and machine weights may differ when options are added





# ROUGH TERRAIN SCISSOR LIFTS

## LIST PRICING (USD) EFFECTIVE JANUARY 1ST, 2025

### SJ6826 RT..... \$65,410

- 26' (7.92 m) Raised platform height
- 1,250 lbs (567 kg) Capacity
- 69.5" (1.76 m) Overall width
- 107" (2.72 m) Overall length
- 63.5" (1.61 m) Stowed height (rails down)
- 56" x 96" (1.42 x 2.44 m) Platform size (inside)

### SJ6832 RT..... \$72,815

- 32' (9.75 m) Raised platform height
- 1,000 lbs (454 kg) Capacity
- 69.5" (1.76 m) Overall width
- 107" (2.72 m) Overall length
- 69" (1.75 m) Stowed height (rails down)
- 56" x 96" (1.42 x 2.44 m) Platform size (inside)

### Standard Features

- Crossover symmetrical 4WD
- Drivable at full height with roll out deck fully extended
- Shroud style, impact resistant composite control box
- 5' (1.52 m) Roll out extension deck
- Dual fuel (gas/propane) or diesel engine
- 90° swing out engine tray
- Multiple wet disc spring applied hydraulic release brakes
- 110V AC outlet on platform with GFI
- Up to 45% Gradeability
- Foam-filled low profile grip lug tires
- Tilt sensor (4.5° x 2.5°)
- Tilt alarm with drive & lift cut-out
- Lanyard attachment points
- All motion audible alarm
- Operator horn
- Hinged railing system
- Forklift pockets and tie down/lift lugs
- Overload sensing system
- Fold down hinged railing system
- Full height spring hinged entry gate at rear of unit
- SKYCODED™ color coded and numbered wiring
- Telematics ready
- 2 Year Gold Leaf Warranty (5 year structural warranty)

### Options†

Independent/auto leveling outriggers .....	\$12,620
Flashing light.....	\$340
3.5 kW generator .....	\$5,925
Cold weather start package .....	\$1,545
(Includes hydraulic oil tank heater, battery blanket, coolant or block heater)	
Positive air shut-off valve.....	\$4,485
Bio oil.....	\$1,830
Secondary guarding lift enable (SGLE) .....	\$365
Non destructive testing .....	\$1,595
White noise alarm .....	\$345
Foam-filled Non-marking tires.....	\$1,795

† Standard lead times may be increased when optional equipment is added, consult factory

\*\* Capacities, and machine weights may differ when options are added



# ROUGH TERRAIN SCISSOR LIFTS

## LIST PRICING (USD) EFFECTIVE JANUARY 1ST, 2025

### SJ9233 RT..... \$114,495

- 33' (10.06 m) Raised platform height
- 2,750 lbs (1,247 kg) Capacity
- 90.6" (2.30 m) Overall width
- 174" (4.42 m) Overall length
- 75" x 170" (1.90 x 4.31 m) Platform size (inside)
- 5' (1.52 m) Roll out extension deck

### SJ9243 RT..... \$118,115

- 43' (13.11 m) Raised platform height
- 2,000 lbs (907 kg) Capacity
- 90.6" (2.30 m) Overall width
- 174" (4.42 m) Overall length
- 75" x 170" (1.90 x 4.31 m) Platform size (inside)
- 5' (1.52 m) Roll out extension deck

### Standard Features

- AXLDRIVE™ Axle-based 4WD system
- Operator controlled locking rear differential and limited slip front differential
- Drivable at full height
- 40% gradeability
- Wet disc SAHR brakes (rear axle)
- SKYCODED™ Color coded and numbered wiring system
- On-board visual interface with diagnostic capabilities
- Kubota D1305 Tier 4F diesel engine
- Self-centering scissor design to support optional dual extension decks
- Lockable power disconnect switch
- Flashing light
- Proportional controls
- Up to 2,750 lbs (1,247 kg) capacity
- Oversized platform with optimal clearance over side of machine
- Fold down hinged railing system
- Full height entry gates
- 5' (1.52 m) roll-out extension deck
- High strength and impact resistant composite control box
- Overload sensing system
- 110V AC Outlet on platform with GFI
- Tilt alarm (4.5° x 2.5°) with drive and lift cut-out
- Single point emergency lowering
- Hourmeter
- Operator horn
- All motion alarm
- Tie down/lifting lugs
- Grip lug solid tires
- Telematics ready
- 2 Year Gold Leaf Warranty (5 year structural warranty)

### Options†

Kubota WG972 dual fuel engine.....	\$2,950
Dual 5' (1.52 m) roll out extension decks .....	\$4,935
Auto leveling outriggers .....	\$13,895
3.5 kW belt driven generator .....	\$6,850
Welder ready package.....	\$14,365
<small>(Includes 7.5 kW hydraulic generator, hydraulic oil cooler, 3-phase power connection in platform)</small>	
Positive air shut-off valve.....	\$4,485
Cold weather start package .....	\$2,075
<small>*Recommended for regions where average monthly low temperatures can reach 14°F / -10°C (Includes hydraulic oil tank heater, battery blanket, coolant or block heater)</small>	
Arctic weather package.....	\$3,675
<small>*Recommended for regions where average monthly low temperatures can reach -0.4°F / -18°C (Includes cold weather start kit plus 60/40 coolant, arctic engine and gear oil)</small>	
Bio oil.....	\$2,105
Secondary guarding lift enable (SGLE) .....	\$365
Non destructive testing .....	\$1,595
White noise alarm .....	\$345
Grip-lug solid non-marking tires.....	\$1,295

† Standard lead times may be increased when optional equipment is added, consult factory

\*\* Capacities, and machine weights may differ when options are added



# ROUGH TERRAIN SCISSOR LIFTS

## LIST PRICING (USD) EFFECTIVE JANUARY 1ST, 2025

### SJ9253 RT..... \$147,625

- 53' (16.15 m) Raised platform height
- 1,500 lbs (680 kg) Capacity
- 90.6" (2.30 m) Overall width
- 174" (4.42 m) Overall length
- 75" x 170" (1.90 x 4.31 m) Platform size (inside)
- 5' (1.52 m) Roll out extension deck

### SJ9664 RT..... \$183,935

- 64' (19.51 m) Raised platform height
- 1,130 lbs (513 kg) Capacity
- 96" (2.44 m) Overall width
- 180" (4.57 m) Overall length
- 75" x 170" (1.90 x 4.31 m) Platform size (inside)
- 5' (1.52 m) Roll out extension deck

### Standard Features

- AXLDRIIVE™ Axle-based 4WD system
- Operator controlled locking rear differential and limited slip front differential
- Drivable at 33' (10.06 m) on SJ9253 RT, 30' (9.14 m) on SJ9664 RT
- Up to 32% gradeability
- Wet disc SAHR brakes (rear axle)
- SKYCODED™ Color coded and numbered wiring system
- On-board visual interface with diagnostic capabilities
- Kubota D1305 Tier 4F diesel engine
- Auto leveling outriggers
- Self-centering scissor design to support optional dual extension decks
- Lockable power disconnect switch
- Flashing light
- Proportional controls
- Up to 1,500 lbs (680 kg) capacity
- Oversized platform with optimal clearance over side of machine
- Fold down hinged railing system
- Full height entry gates
- 5' (1.52 m) roll-out extension deck
- High strength and impact resistant composite control box
- Overload sensing system
- 110V AC Outlet on platform with GFI
- Tilt alarm (4.5° x 2.5°) with drive and lift cut-out
- Single point emergency lowering
- Hourmeter
- Operator horn
- All motion alarm
- Tie down/lifting lugs
- Grip lug solid tires
- Telematics ready
- 2 Year Gold Leaf Warranty (5 year structural warranty)

### Options†

Kubota WG972 dual fuel engine (SJ9253 RT).....	\$2,950
Dual 5' (1.52 m) roll out extension decks .....	\$4,935
3.5 kW generator .....	\$6,850
Welder ready package.....	\$14,365
(Includes 7.5 kW generator, hydraulic oil cooler, 3-phase power connection in platform)	
Positive air shut-off valve.....	\$4,485
Cold weather start package .....	\$2,075
*Recommended for regions where average monthly low temperatures can reach 14°F / -10°C (Includes hydraulic oil tank heater, battery blanket, coolant or block heater)	
Arctic weather package.....	\$3,675
*Recommended for regions where average monthly low temperatures can reach -0.4°F / -18°C (Includes cold weather start kit plus 60/40 coolant, arctic engine and gear oil)	
Bio oil.....	\$2,105
Secondary guarding lift enable (SGLE) .....	\$365
Non destructive testing .....	\$1,595
White noise alarm .....	\$345
Grip-lug solid non-marking tires.....	\$1,295

† Standard lead times may be increased when optional equipment is added, consult factory

\*\* Capacities, and machine weights may differ when options are added



# ARTICULATING BOOM LIFTS

LIST PRICING (USD) EFFECTIVE JANUARY 1ST, 2025

## SJ30 ARJE..... \$103,850

- 29' 6" (9.00 m) Platform height
- 4' 1" (1.25 m) Jib
- 180° Horizontal Jib Rotation
- 500 lbs (227 kg) Capacity
- 20' 7" (6.26 m) Horizontal reach
- 13' 1" (3.99 m) Up and over height
- 355° Non-continuous turret rotation
- 30" x 46" (0.76 x 1.17 m) Platform size

### Standard Features

- EASYDRIVE™ Direction sensing drive and steer controls
- SKYRISER™ True vertical rise
- Direct AC electric drive
- Dual spring applied, electromagnetically released brakes
- Speed and angle sensing traction control
- Drivable at full height
- 35% Gradeability
- Relay based control system with SKYCODED™ color coded and numbered wiring
- 48V 305 Ah Battery pack
- Swing out battery trays
- Swing out cowlings for easy access
- Proportional controls
- Function speed selector
- Rotating jib
- 30" x 46" Platform
- Bolt-in platform railing system
- Lanyard attachment points
- Rear-entry sliding mid rail
- Secondary Guarding Electrical (SGE)
- Overload sensing system
- 110V AC Outlet on platform with GFI
- Tilt alarm (3.0° x 2.0°) with drive and lift cut-out
- Powered emergency lowering
- Hourmeter
- Operator horn
- All motion alarm
- 355° Non-continuous turret rotation
- Tie down/lifting lugs
- Solid rubber, non-marking tires
- Telematics ready
- 2 Year Gold Leaf Warranty (5 year structural warranty)

### Options‡

360 Ah batteries.....	\$835
Rear spring hinged entry gate .....	\$435
Bio oil.....	\$470
Flashing light .....	\$330
White noise alarm .....	\$345

‡ Standard lead times may be increased when optional equipment is added, consult factory

\*\* Capacities, and machine weights may differ when options are added



# ARTICULATING BOOM LIFTS

LIST PRICING (USD) EFFECTIVE JANUARY 1ST, 2025

## SJ45 AJ+ ..... \$136,025

- 45' (13.72 m) Platform height
- 4'8" (1.4 m) Jib
- 660 lbs (300 kg) Capacity
- 22' 9" (6.93 m) Horizontal reach
- 24' 5.25" (7.45 m) Up and over height
- 355° Non-continuous turret rotation
- 30" x 72" (0.76 x 1.83 m) Platform size

### Standard Features

- EASYDRIVE™ Direction sensing drive and steer controls
- SKYRISER™ True vertical rise
- AXLDRIVE™ Axle-based 4WD system
- Operator controlled locking rear differential and limited slip front differential
- Oscillating steer axle
- Drivable at full height
- 40% Gradeability
- Wet disc SAHR brakes (rear axle)
- Dual module control system with SKYCODED™ color coded and numbered wiring
- Kubota D1305 Tier 4F diesel engine
- Swing up cowlings for easy access
- Lockable power disconnect switch
- Proportional controls
- 660 lbs (300 kg) Capacity
- 30 x 72" Platform
- Bolt-in platform railing system
- Lanyard attachment points
- Dual-entry sliding mid rails
- Secondary Guarding Electrical (SGE)
- Overload sensing system
- 110V AC Outlet on platform with GFI
- Tilt alarm (5.0° x 5.0°) with drive and lift cut-out
- Single point emergency lowering
- Hourmeter
- Operator horn
- All motion alarm
- 355° Non-continuous turret rotation
- Tie down/lifting lugs
- Grip lug solid tires
- Telematics ready
- 2 Year Gold Leaf Warranty (5 year structural warranty)

### Options†

Kubota WG972 dual fuel engine .....	\$2,950
Flashing light .....	\$870
Side spring hinged entry gate.....	\$435
3.5 kW generator .....	\$6,850
Welder ready package.....	\$14,365
<small>(Includes 7.5 kW generator, 3-phase power connection in platform, and welder mount)</small>	
Cold weather start kit* .....	\$3,200
<small>*Recommended for regions where average monthly low temperatures can reach 14°F / -10°C (Includes cold start engine oil, battery blanket, and hydraulic tank heater)</small>	
Arctic weather package* .....	\$4,805
<small>*Recommended for regions where average monthly low temperatures can reach -0.4°F / -18°C (Includes arctic engine oil, battery blanket, hydraulic tank heater, block heater, arctic hydraulic oil, and arctic gear oil in the axles and swing drive. Glow plugs, arctic hydraulic hoses (all), arctic platform rotator and oversized foot switch cover are also included (standard equipment).)</small>	
Positive air shut-off valve (diesel only) .....	\$4,485
Bio oil .....	\$3,200
White noise alarm .....	\$345
Grip lug solid non-marking tires.....	\$1,295
Turf foam-filled tires.....	\$10,215

‡ Standard lead times may be increased when optional equipment is added, consult factory

\*\* Capacities, and machine weights may differ when options are added



# ARTICULATING BOOM LIFTS

LIST PRICING (USD) EFFECTIVE JANUARY 1ST, 2025

## SJ60 AJ+..... \$198,650

- 60' (18.29 m) Platform height
- 5' (1.52 m) Jib
- 660 / 1,000 lbs (300 / 454 kg) Dual capacity
- 37'11" (11.56 m) Horizontal reach
- 27' 2" (8.31 m) Up and over height
- 360° Continuous Turret Rotation
- 36" x 96" (0.91 x 2.44 m) Platform size

### Standard Features

- EASYDRIVE™ Direction sensing drive and steer controls
- SPEEDYREACH™ Negative boom angle capability
- SKYRISER™ True vertical rise
- AXLDRIVE™ Axle-based 4WD system
- Operator controlled locking rear differential and limited slip front differential
- Oscillating steer axle
- Drivable at full height
- 38% Gradeability
- Wet disc SAHR brakes (front and rear axle)
- Dual module control system with SKYCODED™ color coded and numbered wiring
- Kubota D1305 Tier 4F diesel engine
- Swing up cowlings for easy access
- Lockable power disconnect switch
- Proportional controls
- 660 / 1,000 lbs (300 / 454 kg) Dual capacity
- 36" x 96" Platform
- Bolt-in platform railing system
- Lanyard attachment points
- Tri-entry sliding mid-rails
- Secondary Guarding Electrical (SGE)
- Overload sensing system
- 110V AC Outlet on platform with GFI
- Tilt alarm (5.0° x 5.0°) with drive and lift cut-out
- Single point emergency lowering
- Hourmeter
- Operator horn
- All motion alarm
- 360° Continuous turret rotation
- Tie down/lifting lugs
- Grip lug foam-filled tires
- Telematics ready
- 2 Year Gold Leaf Warranty (5 year structural warranty)

### Options†

Kubota WG972 dual fuel engine.....	\$2,950
Flashing light .....	\$870
Side spring hinged entry gate.....	\$435
3.5 kW generator .....	\$6,850
Welder ready package.....	\$14,365
<small>(Includes 7.5 kW generator, 3-phase power connection in platform, and welder mount)</small>	
Cold weather start kit* .....	\$3,200
<small>*Recommended for regions where average monthly low temperatures can reach 14°F / -10°C (Includes cold start engine oil, battery blanket, and hydraulic tank heater)</small>	
Arctic weather package* .....	\$4,805
<small>†Recommended for regions where average monthly low temperatures can reach -0.4°F / -18°C (Includes arctic engine oil, battery blanket, hydraulic tank heater, block heater, arctic hydraulic oil, and arctic gear oil in the axles and swing drive. Glow plugs, arctic hydraulic hoses (all), arctic platform rotator and oversized foot switch cover are also included (standard equipment).)</small>	
Positive air shut-off valve (diesel only) .....	\$4,485
Bio oil.....	\$3,565
White noise alarm .....	\$345
Grip lug foam-filled non marking tires.....	\$1,790
Turf foam-filled tires.....	\$10,215

‡ Standard lead times may be increased when optional equipment is added, consult factory

\*\* Capacities, and machine weights may differ when options are added



# ARTICULATING BOOM LIFTS

LIST PRICING (USD) EFFECTIVE JANUARY 1ST, 2025

**SJ85 AJ..... \$291,430**

- 85' (25.91 m) Platform height
- 5'6" (1.68 m) Jib
- 500 / 750 lbs (227 / 341 kg) Dual capacity
- 56' (17.07 m) Horizontal reach
- 34' (10.36 m) Up and over height
- 360° Continuous Turret Rotation
- 36" x 96" (0.91 x 2.44 m) Platform size

## Standard Features

- EASYDRIVE™ Direction sensing drive and steer controls
- SPEEDYREACH™ Negative boom angle capability
- SKYRISER™ True vertical rise
- AXLDRIVE™ Axle-based 4WD system
- Operator controlled locking rear differential and limited slip front differential
- Oscillating steer axle
- Drivable at full height
- 45% Gradeability
- Wet disc SAHR brakes (front and rear axle)
- Relay based control system with SKYCODED™ color coded and numbered wiring
- Deutz TD2.9L4 diesel engine
- Swing out engine tray
- Swing up cowlings for easy access
- Lockable power disconnect switch
- Proportional controls
- 500 / 750 lbs (227 / 341 kg) Dual capacity
- 36" x 96" Platform
- Bolt-in platform railing system
- Lanyard attachment points
- Tri-entry sliding mid-rails
- Secondary Guarding Electrical (SGE)
- Overload sensing system
- 110V AC Outlet on platform with GFI
- Tilt alarm (5.0° x 5.0°) with drive and lift cut-out
- Single point emergency lowering
- Hourmeter
- Operator horn
- All motion alarm
- 360° Continuous turret rotation
- Tie down/lifting lugs
- Grip lug foam-filled tires
- Telematics ready
- 2 Year Gold Leaf Warranty (5 year structural warranty)

## Options†

Kubota WG3800 dual fuel engine.....	<b>\$730</b>
Flashing light .....	<b>\$870</b>
Side spring hinged entry gate.....	<b>\$435</b>
3.5 kW generator .....	<b>\$6,850</b>
<small>(Includes hydraulic oil cooler)</small>	
Welder ready package.....	<b>\$14,365</b>
<small>(Includes 12 kW generator, hydraulic oil cooler, 3-phase power connection in platform, and welder mount)</small>	
Cold weather start kit* .....	<b>\$3,200</b>
<small>*Recommended for regions where average monthly low temperatures can reach 14°F / -10°C</small>	
<small>(Includes cold start engine oil, battery blanket, hydraulic tank heater, and engine load kit (Deutz TD2.9L4))</small>	
Arctic weather package* .....	<b>\$4,805</b>
<small>*Recommended for regions where average monthly low temperatures can reach -0.4°F / -18°C</small>	
<small>(Includes arctic engine oil, battery blanket, hydraulic tank heater, engine load kit (Deutz TD2.9L4), block heater, arctic hydraulic oil, arctic platform rotator and arctic gear oil in the axles and swing drive. Glow plugs, arctic hydraulic hoses (all), and oversized foot switch cover are also included (standard equipment).)</small>	
Hydraulic oil cooler .....	<b>\$2,390</b>
Positive air shut-off valve (diesel only) .....	<b>\$4,485</b>
Bio oil.....	<b>\$5,960</b>
White noise alarm .....	<b>\$345</b>
Grip lug foam-filled non marking tires.....	<b>\$1,790</b>

‡ Standard lead times may be increased when optional equipment is added, consult factory

\*\* Capacities, and machine weights may differ when options are added



# TELESCOPIC BOOM LIFTS

LIST PRICING (USD) EFFECTIVE JANUARY 1ST, 2025

## SJ40 T+ ..... \$148,915

- 40' 7" (12.37 m) Platform height
- 750 / 1,000 lbs (340 / 454 kg) Dual capacity
- 33' 11" (10.34 m) Horizontal reach
- 170° Platform rotation
- 36" x 96" (0.91 x 2.44 m) Platform size

## SJ45 T+ ..... \$161,410

- 45' 1.5" (13.75 m) Platform height
- 5' (1.52 m) Jib
- 660 / 1,000 lbs (300 / 454 kg) Dual capacity
- 39' 8.25" (12.10 m) Horizontal reach
- 170° Platform rotation
- 36" x 96" (0.91 x 2.44 m) Platform size

### Standard Features

- EASYDRIVE™ Direction sensing drive and steer controls
- AXLDRIIVE™ Axle-based 4WD system
- Operator controlled locking rear differential and limited slip front differential
- Oscillating steer axle
- Drivable at full height
- 40% Gradeability
- Wet disc SAHR brakes (rear axle)
- Dual module control system with SKYCODED™ color coded and numbered wiring
- Kubota D1305 Tier 4F diesel engine
- Swing up cowlings for easy access
- Lockable power disconnect switch
- Proportional controls
- Up to 750 / 1,000 lbs (340 / 454 kg) Dual capacity
- 36" x 96" Platform
- Bolt-in platform railing system
- Lanyard attachment points
- Tri-entry sliding mid rails
- Secondary Guarding Electrical (SGE)
- Overload sensing system
- 110V AC Outlet on platform with GFI
- Tilt alarm (5.0° x 5.0°) with drive and lift cut-out
- Single point emergency lowering
- Hourmeter
- Operator horn
- All motion alarm
- 360° Continuous turret rotation
- Tie down/lifting lugs
- Grip lug solid tires
- Telematics ready
- 2 Year Gold Leaf Warranty (5 year structural warranty)

### Options†

Flashing light .....	\$870
Side spring hinged entry gate.....	\$435
3.5 kW generator.....	\$6,850
Welder ready package.....	\$14,365
<small>(Includes 7.5 kW generator, 3-phase power connection in platform, and welder mount)</small>	
Cold weather start kit* .....	\$3,200
<small>*Recommended for regions where average monthly low temperatures can reach 14°F / -10°C (Includes cold start engine oil, battery blanket, and hydraulic tank heater)</small>	
Arctic weather package* .....	\$4,805
<small>*Recommended for regions where average monthly low temperatures can reach -0.4°F / -18°C (Includes arctic engine oil, battery blanket, hydraulic tank heater, block heater, arctic hydraulic oil, and arctic gear oil in the axles and swing drive. Glow plugs, arctic hydraulic hoses (all), arctic platform rotator and oversized foot switch cover are also included (standard equipment).)</small>	
Positive air shut-off valve (diesel only) .....	\$4,485
Bio oil.....	\$6,210
White noise alarm .....	\$345
Grip lug solid non-marking tires.....	\$1,295
Turf foam-filled tires.....	\$10,215

† Standard lead times may be increased when optional equipment is added, consult factory

\*\* Capacities, and machine weights may differ when options are added





# TELESCOPIC BOOM LIFTS

LIST PRICING (USD) EFFECTIVE JANUARY 1ST, 2025

## SJ61 T+ ..... \$212,965

- 61' 8" (18.80 m) Platform height
- 660 / 1,000 lbs (300 / 454 kg) Dual capacity
- 51' 3" (15.62 m) Horizontal reach
- 170° Platform rotation
- 36" x 96" (0.91 x 2.44 m) Platform size

## SJ66 T+ ..... \$224,945

- 66' 3" (20.19 m) Platform height
- 5' (1.52 m) Jib
- 660 / 1,000 lbs (300 / 454 kg) Dual capacity
- 57' 0.25" (17.38 m) Horizontal reach
- 170° Platform rotation
- 36" x 96" (0.91 x 2.44 m) Platform size

### Standard Features

- EASYDRIVE™ Direction sensing drive and steer controls
- AXLDRIIVE™ Axle-based 4WD system
- Operator controlled locking rear differential and limited slip front differential
- Oscillating steer axle
- Drivable at full height
- 50% Gradeability
- Wet disc SAHR brakes (front and rear axle)
- Dual module control system with SKYCODED™ color coded and numbered wiring
- Deutz TD2.9L4 diesel engine
- Swing out engine tray
- Swing up cowlings for easy access
- Lockable power disconnect switch
- Proportional controls
- 660 / 1,000 lbs (300 / 454 kg) Dual capacity
- 36" x 96" Platform
- Bolt-in platform railing system
- Lanyard attachment points
- Tri-entry sliding mid rails
- Secondary Guarding Electrical (SGE)
- Overload sensing system
- 110V AC Outlet on platform with GFI
- Tilt alarm (5.0° x 5.0°) with drive and lift cut-out
- Single point emergency lowering
- Hourmeter
- Operator horn
- All motion alarm
- 360° Continuous turret rotation
- Tie down/lifting lugs
- Grip lug foam-filled tires
- Telematics ready
- 2 Year Gold Leaf Warranty (5 year structural warranty)

### Options†

Kubota WG2503 dual fuel engine.....	N/C
Flashing light .....	\$870
Side spring hinged entry gate.....	\$435
3.5 kW generator .....	\$6,850
<small>(Includes hydraulic oil cooler)</small>	
Welder ready package.....	\$14,365
<small>(Includes 12 kW generator, hydraulic oil cooler, 3-phase power connection in platform, and welder mount)</small>	
Cold weather start kit* .....	\$3,200
<small>*Recommended for regions where average monthly low temperatures can reach 14°F / -10°C (Includes cold start engine oil, battery blanket, hydraulic tank heater, and engine load kit (Deutz TD2.9L4))</small>	
Arctic weather package* .....	\$4,805
<small>*Recommended for regions where average monthly low temperatures can reach -0.4°F / -18°C (Includes arctic engine oil, battery blanket, hydraulic tank heater, engine load kit (Deutz TD2.9L4), block heater, arctic hydraulic oil, arctic platform rotator and arctic gear oil in the axles and swing drive. Glow plugs, arctic hydraulic hoses (all), and oversized foot switch cover are also included (standard equipment).)</small>	
Hydraulic oil cooler .....	\$2,390
Positive air shut-off valve (diesel only) .....	\$4,485
Bio oil.....	\$6,195
White noise alarm .....	\$345
Grip lug foam-filled non marking tires.....	\$2,150
Turf foam-filled tires.....	\$12,535

† Standard lead times may be increased when optional equipment is added, consult factory

\*\* Capacities, and machine weights may differ when options are added



# TELESCOPIC BOOM LIFTS

LIST PRICING (USD) EFFECTIVE JANUARY 1ST, 2025

## SJ82 T..... \$295,315

- 82' (24.99 m) Platform height
- 500 / 750 lbs (227 / 341 kg) Dual capacity
- 72'6" (22.10 m) Horizontal reach
- 170° Platform rotation
- 36" x 96" (0.91 x 2.44 m) Platform size

## SJ86 T..... \$307,590

- 86' (26.21 m) Platform height
- 5' 6" (1.68 m) Jib
- 500 / 750 lbs (227 / 341 kg) Dual capacity
- 76'10" (23.42 m) Horizontal reach
- 170° Platform rotation
- 36" x 96" (0.91 x 2.44 m) Platform size

### Standard Features

- EASYDRIVE™ Direction sensing drive and steer controls
- AXLDRIIVE™ Axle-based 4WD system
- Operator controlled locking rear differential and limited slip front differential
- Oscillating steer axle
- Drivable at full height
- 45% Gradeability
- Wet disc SAHR brakes (front and rear axle)
- Relay based control system with SKYCODED™ color coded and numbered wiring
- Deutz TD2.9L4 diesel engine
- Swing out engine tray
- Swing up cowlings for easy access
- Lockable power disconnect switch
- Proportional controls
- 500 / 750 lbs (227 / 341 kg) Dual capacity
- 36" x 96" Platform
- Bolt-in platform railing system
- Lanyard attachment points
- Tri-entry sliding mid rails
- Secondary Guarding Electrical (SGE)
- Overload sensing system
- 110V AC Outlet on platform with GFI
- Tilt alarm (5.0° x 5.0°) with drive and lift cut-out
- Single point emergency lowering
- Hourmeter
- Operator horn
- All motion alarm
- 360° Continuous turret rotation
- Tie down/lifting lugs
- Grip lug foam filled tires
- Telematics ready
- 2 Year Gold Leaf Warranty (5 year structural warranty)

### Options†

Flashing light .....	\$870
Side spring hinged entry gate.....	\$435
3.5 kW generator .....	\$6,850
<small>(Includes hydraulic oil cooler)</small>	
Welder ready package.....	\$14,365
<small>(Includes 12 kW generator, hydraulic oil cooler, 3-phase power connection in platform, and welder mount)</small>	
Cold weather start kit* .....	\$3,200
<small>*Recommended for regions where average monthly low temperatures can reach 14°F / -10°C (Includes cold start engine oil, battery blanket, hydraulic tank heater, and engine load kit (Deutz TD2.9L4))</small>	
Arctic weather package* .....	\$4,805
<small>*Recommended for regions where average monthly low temperatures can reach -0.4°F / -18°C (Includes arctic engine oil, battery blanket, hydraulic tank heater, engine load kit (Deutz TD2.9L4), block heater, arctic hydraulic oil, arctic platform rotator and arctic gear oil in the axles and swing drive. Glow plugs, arctic hydraulic hoses (all), and oversized foot switch cover are also included (standard equipment).)</small>	
Hydraulic oil cooler .....	\$2,390
Positive air shut-off valve (diesel only) .....	\$4,485
Bio oil.....	\$6,185
White noise alarm .....	\$345
Grip lug foam-filled non marking tires.....	\$2,150

† Standard lead times may be increased when optional equipment is added, consult factory

\*\* Capacities, and machine weights may differ when options are added



# TELEHANDLERS

LIST PRICING (USD) EFFECTIVE JANUARY 1ST, 2025

## SJ519 TH..... \$96,790

- 5,500 lbs (2,500 kg) Maximum lift capacity
- 19'1" (5.82 m) Maximum lift height
- 4,400 lbs (2,000 kg) Capacity @ maximum lift height
- 11'3" (3.44 m) Maximum forward reach
- 2,000 lbs (862 kg) Capacity @ maximum forward reach
- 1.5"x4"x48" Forks
- DPF & DEF Free Tier 4 Final Deutz TCD 2.2L engine
- Hydrostatic transmission
- 3 Mode steering
- 48" Floating pin carriage with 48" Pallet forks
- Air filled 12 x 16.5 grip lug tires

### Standard Features

- Auxiliary hydraulics with hydraulic flow control valve
- Quick attach carriage mount
- Rear and side window
- Suspension seat
- Single multifunction pilot operated joystick control
- In cab engine multifunction display
- Hydraulic test ports
- Lockable in cab storage box
- Steel engine cowling
- Steel component and access covers
- Telematics ready
- 2 Year Gold Leaf Warranty (5 year structural warranty)

### Forks‡

Pallet, 1.5"x4"x48", 5,500lbs capacity .....	<b>STD</b>
Pallet, 1.5"x4"x60", 5,500lbs capacity (In lieu of standard) .....	<b>\$235</b>
For additional set of forks add to in lieu of price.....	<b>\$1,180</b>

### Carriages‡

48" Floating pin carriage .....	<b>STD</b>
48" Side tilt (In lieu of standard).....	<b>\$3,465</b>
For additional carriage add to in lieu of price .....	<b>\$2,065</b>
Hydraulic carriage connect .....	<b>\$1,335</b>

### Options‡

Closed cab .....	<b>\$4,465</b>
FLEXDRIVE™ drive speed select dial .....	<b>\$270</b>
Tilt steering .....	<b>\$615</b>
Air conditioning .....	<b>\$3,650</b>
Four wheel fenders .....	<b>\$2,245</b>
Road lights .....	<b>\$1,170</b>
Boom lights.....	<b>\$815</b>
Work lights .....	<b>\$815</b>
Rotating beacon .....	<b>\$405</b>
Back up sensor .....	<b>\$2,490</b>
Back up camera & sensor .....	<b>\$5,855</b>
Block heater.....	<b>\$375</b>
Cold weather package .....	<b>\$1,190</b>
<small>(Includes cold start engine oil, block heater, battery blanket &amp; hydraulic tank heater)</small>	
Service convenience package .....	<b>\$295</b>
<small>(Includes remote axle grease points &amp; clean drain oil valve)</small>	
White noise alarm .....	<b>\$345</b>

### Tire Options‡

Foam filled 12 x 16.5 grip lug (In lieu of standard) .....	<b>\$3,120</b>
Airless solid rubber 33 x 12 (In lieu of standard) .....	<b>\$4,400</b>
Non-marking airless solid rubber 33 x 12 (In lieu of standard) .....	<b>\$5,450</b>
Turf air-filled tires (In lieu of standard) .....	<b>\$4,400</b>

‡ Standard lead times may be increased when optional equipment is added, consult factory

\*\* Capacities, and machine weights may differ when options are added



# TELEHANDLERS

LIST PRICING (USD) EFFECTIVE JANUARY 1ST, 2025

## SJ643 TH..... \$147,660

- 6,000 lbs (2,722 kg) Maximum lift capacity
- 43'4" (13.2 m) Maximum lift height
- 6,000 lbs (2,722 kg) Capacity @ maximum lift height
- 28'7" (8.7 m) Maximum forward reach
- 1,000 lbs (454 kg) Capacity @ maximum forward reach
- 2"x4"x48" Forks
- DPF & DEF Free Tier 4 Final 74 hp/221 lb-ft Deutz TCD 2.2L engine
- Powershift, 3 speed transmission
- 3 Mode steering
- 48" Floating pin carriage with 48" Pallet forks
- Foam filled 13 x 24 rough terrain tires

### Standard Features

- Auxiliary hydraulics
- Engine block heater
- Quick attach carriage mount
- Rear window with wiper
- Side window
- Suspension seat
- Single multifunction pilot operated joystick control
- In cab engine multifunction display
- Hydraulic test ports
- Lockable in cab storage box
- Steel engine cowling
- Steel component and access covers
- Telematics ready
- 2 Year Gold Leaf Warranty (5 year structural warranty)

### Forks‡

Pallet 2"x4"x48", 8,000lbs capacity .....	<b>STD</b>
Pallet 2"x4"x60", 8,000lbs capacity (In lieu of standard) .....	<b>\$375</b>
Pallet 2"x5"x48", 9,200lbs capacity (In lieu of standard) .....	<b>\$165</b>
Pallet 2"x5"x60", 9,200lbs capacity (In lieu of standard) .....	<b>\$350</b>
Pallet 2.25"x5"x48", 12,000lbs capacity (In lieu of standard) .....	<b>\$670</b>
Pallet 2.25"x5"x60", 12,000lbs capacity (In lieu of standard) .....	<b>\$785</b>
Pallet 2.25"x5"x72", 12,000lbs capacity (In lieu of standard) .....	<b>\$1,300</b>

For additional set of forks add to in lieu of price..... **\$1,305**

### Carriages‡

48" Floating pin carriage .....	<b>STD</b>
60" Floating pin (In lieu of standard).....	<b>\$885</b>
72" Floating pin (In lieu of standard).....	<b>\$1,685</b>
72" Floating pin (SJ1256 THS carriage) (In lieu of standard).....	<b>\$2,360</b>
48" Floating pin, side tilting (In lieu of standard) .....	<b>\$3,540</b>
60" Floating pin, side tilting (In lieu of standard) .....	<b>\$4,430</b>
72" Floating pin, side tilting (In lieu of standard) .....	<b>\$5,045</b>
72" Swing carriage (In lieu of standard).....	<b>\$6,950</b>

For additional carriage add to in lieu of price .....

### Options‡

Closed cab .....	<b>\$6,260</b>
Air conditioning (Closed cab only) .....	<b>\$4,165</b>
Premium joystick.....	<b>\$3,605</b>
Four wheel fenders.....	<b>\$2,300</b>
Road lights .....	<b>\$1,150</b>
Work lights .....	<b>\$1,185</b>
Boom lights.....	<b>\$435</b>
Rotating beacon .....	<b>\$395</b>
Backup sensor .....	<b>\$2,450</b>
Backup sensor and camera .....	<b>\$5,755</b>
Cold weather package .....	<b>\$1,105</b>
<small>(Includes cold start engine oil, battery blanket &amp; hydraulic tank heater)</small>	
Arctic weather package .....	<b>\$2,585</b>
<small>(Includes cold start engine oil, battery blanket &amp; hydraulic tank heater, arctic hydraulic oil)</small>	
Service convenience package .....	<b>\$350</b>
<small>(Includes remote axle grease points &amp; clean drain oil valve)</small>	
Pintle hitch.....	<b>\$660</b>
White noise alarm .....	<b>\$345</b>

### Tire Options‡

Airless solid rubber 13 x 24 (In lieu of standard) .....	<b>\$6,625</b>
Non-marking airless solid rubber 13 x 24 (In lieu of standard) .....	<b>\$12,105</b>



‡ Standard lead times may be increased when optional equipment is added, consult factory

\*\* Capacities, and machine weights may differ when options are added

This literature is for illustrative purposes only. Consult the Operating, Service and Parts manuals for proper procedures. Telehandler machine design complies with ANSI/ITSDF B56.6-2005 stability requirements for rough terrain forklifts. Specifications are nominal and subject to change without notice. Pricing is subject to change without notice. Option and Attachment pricing valid only with new equipment purchases.

# TELEHANDLERS

LIST PRICING (USD) EFFECTIVE JANUARY 1ST, 2025

## SJ843 TH..... \$159,245

- 8,000 lbs (3,629 kg) Maximum lift capacity
- 43'4" (13.2 m) Maximum lift height
- 6,000 lbs (2,722 kg) Capacity @ maximum lift height
- 28'7" (8.7 m) Maximum forward reach
- 1,900 lbs (862 kg) Capacity @ maximum forward reach
- 2"x4"x48" Forks
- DPF & DEF Free Tier 4 Final 74 hp/221 lb-ft Deutz TCD 2.2L engine
- Powershift, 3 speed transmission
- 3 Mode steering
- 48" Floating pin carriage with 48" Pallet forks
- Foam filled 13 x 24 rough terrain tires

### Standard Features

- Auxiliary hydraulics
- Engine block heater
- Quick attach carriage mount
- Rear window with wiper
- Side window
- Suspension seat
- Single multifunction pilot operated joystick control
- In cab engine multifunction display
- Hydraulic test ports
- Lockable in cab storage box
- Steel engine cowling
- Steel component and access covers
- Telematics ready
- 2 Year Gold Leaf Warranty (5 year structural warranty)

### Forks‡

Pallet 2"x4"x48", 8,000lbs capacity .....	<b>STD</b>
Pallet 2"x4"x60", 8,000lbs capacity (In lieu of standard) .....	<b>\$375</b>
Pallet 2"x5"x48", 9,200lbs capacity (In lieu of standard) .....	<b>\$165</b>
Pallet 2"x5"x60", 9,200lbs capacity (In lieu of standard) .....	<b>\$350</b>
Pallet 2.25"x5"x48", 12,000lbs capacity (In lieu of standard) .....	<b>\$670</b>
Pallet 2.25"x5"x60", 12,000lbs capacity (In lieu of standard) .....	<b>\$785</b>
Pallet 2.25"x5"x72", 12,000lbs capacity (In lieu of standard) .....	<b>\$1,300</b>

For additional set of forks add to in lieu of price..... **\$1,305**

### Carriages‡

48" Floating pin carriage .....	<b>STD</b>
60" Floating pin (In lieu of standard).....	<b>\$885</b>
72" Floating pin (In lieu of standard).....	<b>\$1,685</b>
72" Floating pin (SJ1256 THS carriage) (In lieu of standard).....	<b>\$2,360</b>
48" Floating pin, side tilting (In lieu of standard) .....	<b>\$3,540</b>
60" Floating pin, side tilting (In lieu of standard) .....	<b>\$4,430</b>
72" Floating pin, side tilting (In lieu of standard) .....	<b>\$5,045</b>
72" Swing carriage (In lieu of standard).....	<b>\$6,950</b>

For additional carriage add to in lieu of price .....

### Options‡

Closed cab .....	<b>\$6,260</b>
Air conditioning (Closed cab only) .....	<b>\$4,165</b>
Premium joystick.....	<b>\$3,605</b>
Four wheel fenders.....	<b>\$2,300</b>
Road lights .....	<b>\$1,150</b>
Work lights .....	<b>\$1,185</b>
Boom lights.....	<b>\$435</b>
Rotating beacon .....	<b>\$395</b>
Backup sensor .....	<b>\$2,450</b>
Backup sensor and camera .....	<b>\$5,755</b>
Cold weather package .....	<b>\$1,105</b>
<small>(Includes cold start engine oil, battery blanket &amp; hydraulic tank heater)</small>	
Arctic weather package .....	<b>\$2,585</b>
<small>(Includes cold start engine oil, battery blanket &amp; hydraulic tank heater, arctic hydraulic oil)</small>	
Service convenience package .....	<b>\$350</b>
<small>(Includes remote axle grease points &amp; clean drain oil valve)</small>	
Pintle hitch.....	<b>\$660</b>
White noise alarm .....	<b>\$345</b>

### Tire Options‡

Airless solid rubber 13 x 24 (In lieu of standard) .....	<b>\$6,625</b>
Non-marking airless solid rubber 13 x 24 (In lieu of standard) .....	<b>\$12,105</b>



‡ Standard lead times may be increased when optional equipment is added, consult factory

\*\* Capacities, and machine weights may differ when options are added

This literature is for illustrative purposes only. Consult the Operating, Service and Parts manuals for proper procedures. Telehandler machine design complies with ANSI/ITSDF B56.6-2005 stability requirements for rough terrain forklifts. Specifications are nominal and subject to change without notice. Pricing is subject to change without notice. Option and Attachment pricing valid only with new equipment purchases.

# TELEHANDLERS

LIST PRICING (USD) EFFECTIVE JANUARY 1ST, 2025

## SJ1044 TH..... \$180,250

- 10,000 lbs (4,535 kg) Maximum lift capacity
- 44'3" (13.49 m) Maximum lift height
- 7,000 lbs (3,175 kg) Capacity @ maximum lift height
- 29'4" (8.94 m) Maximum forward reach
- 1,800 lbs (816 kg) Capacity @ maximum forward reach
- 2.36"x4"x48" Forks
- DPF & DEF Free Tier 4 Final 74 hp/287 lb-ft Deutz TCD 3.6L engine
- Powershift, 3 speed transmission
- 3 Mode steering
- 48" Floating pin carriage with 48" Pallet forks
- Foam filled 14 x 24 rough terrain tires

### Standard Features

- Auxiliary hydraulics
- Engine block heater
- Quick attach carriage mount
- Rear window with wiper
- Side window
- Suspension seat
- Single multifunction pilot operated joystick control
- In cab engine multifunction display
- Hydraulic test ports
- Lockable in cab storage box
- Steel engine cowling
- Steel component and access covers
- Telematics ready
- 2 Year Gold Leaf Warranty (5 year structural warranty)

### Forks‡

Pallet, 2.36"x4"x48", 10,000lbs capacity .....	<b>STD</b>
Pallet, 2.36"x4"x60", 10,000lbs capacity (In lieu of standard) .....	<b>\$250</b>
Pallet, 2.36"x4"x72", 10,000lbs capacity (In lieu of standard) .....	<b>\$600</b>
Pallet, 2.25"x5"x48", 12,000lbs capacity (In lieu of standard) .....	<b>\$175</b>
Pallet, 2.25"x5"x60", 12,000lbs capacity (In lieu of standard) .....	<b>\$445</b>
Pallet, 2.25"x5"x72", 12,000lbs capacity (In lieu of standard) .....	<b>\$940</b>

For additional set of forks add to in lieu of price..... **\$1,540**

### Carriages‡

48" Floating pin carriage .....	<b>STD</b>
60" Floating pin (In lieu of standard) .....	<b>\$885</b>
72" Floating pin (In lieu of standard) .....	<b>\$1,685</b>
72" Floating pin (SJ1256 THS carriage) (In lieu of standard) .....	<b>\$2,360</b>
48" Floating pin, side tilting (In lieu of standard) .....	<b>\$3,540</b>
60" Floating pin, side tilting (In lieu of standard) .....	<b>\$4,430</b>
72" Floating pin, side tilting (In lieu of standard) .....	<b>\$5,045</b>
72" Swing carriage (In lieu of standard) .....	<b>\$6,950</b>

For additional carriage add to in lieu of price .....

### Options‡

Closed cab .....	<b>\$6,260</b>
Air conditioning (Closed cab only) .....	<b>\$4,165</b>
Premium joystick.....	<b>\$3,605</b>
Four wheel fenders.....	<b>\$2,300</b>
Road lights .....	<b>\$1,150</b>
Work lights .....	<b>\$1,185</b>
Boom lights.....	<b>\$435</b>
Rotating beacon .....	<b>\$395</b>
Backup sensor .....	<b>\$2,450</b>
Backup sensor and camera .....	<b>\$5,755</b>
Cold weather package .....	<b>\$1,105</b>
<small>(Includes cold start engine oil, battery blanket &amp; hydraulic tank heater)</small>	
Arctic weather package .....	<b>\$2,585</b>
<small>(Includes cold start engine oil, battery blanket &amp; hydraulic tank heater, arctic hydraulic oil)</small>	
Service convenience package .....	<b>\$350</b>
<small>(Includes remote axle grease points &amp; clean drain oil valve)</small>	
Positive air shut-off valve .....	<b>\$4,485</b>
Pintle hitch.....	<b>\$660</b>
White noise alarm .....	<b>\$345</b>

### Optional Engine‡

107hp Deutz TCD3.6L .....	<b>\$9,100</b>
---------------------------	----------------

### Tire Options‡

Airless solid rubber 13 x 24 (In lieu of standard) .....	<b>\$5,320</b>
Non-marking airless solid rubber 13 x 24 (In lieu of standard) .....	<b>\$10,330</b>

‡ Standard lead times may be increased when optional equipment is added, consult factory

\*\* Capacities, and machine weights may differ when options are added



# TELEHANDLERS

LIST PRICING (USD) EFFECTIVE JANUARY 1ST, 2025

## SJ1056 TH..... \$203,080

- 10,000 lbs (4,535 kg) Maximum lift capacity
- 56'3" (17.1 m) Maximum lift height
- 4,000 lbs (1,814 kg) Capacity @ maximum lift height
- 6,000 lbs (2,722 kg) Capacity @ maximum lift height (on outriggers)
- 42'2" (12.85 m) Maximum forward reach
- 400 lbs (181 kg) Capacity @ maximum forward reach
- 3,000 lbs (1,361 kg) Capacity @ maximum forward reach (on outriggers)
- 2.36"x4"x48" Forks
- DPF & DEF Free Tier 4 Final 74 hp/287 lb-ft Deutz TCD 3.6L engine
- Powershift, 3 speed transmission
- 3 Mode steering
- 48" Floating pin carriage with 48" Pallet forks
- Foam filled 14 x 24 rough terrain tires

### Standard Features

- Axle mounted outriggers
- Auxiliary hydraulics
- Engine block heater
- Quick attach carriage mount
- Rear window with wiper
- Side window
- Suspension seat
- Single multifunction pilot operated joystick control
- In cab engine multifunction display
- Hydraulic test ports
- Lockable in cab storage box
- Steel engine cowling
- Steel component and access covers
- Telematics ready
- 2 Year Gold Leaf Warranty (5 year structural warranty)

### Forks‡

Pallet, 2.36"x4"x48", 10,000lbs capacity .....	<b>STD</b>
Pallet, 2.36"x4"x60", 10,000lbs capacity (In lieu of standard) .....	<b>\$250</b>
Pallet, 2.36"x4"x72", 10,000lbs capacity (In lieu of standard) .....	<b>\$600</b>
Pallet, 2.25"x5"x48", 12,000lbs capacity (In lieu of standard) .....	<b>\$175</b>
Pallet, 2.25"x5"x60", 12,000lbs capacity (In lieu of standard) .....	<b>\$445</b>
Pallet, 2.25"x5"x72", 12,000lbs capacity (In lieu of standard) .....	<b>\$940</b>
For additional set of forks add to in lieu of price.....	<b>\$1,540</b>

### Carriages‡

48" Floating pin carriage .....	<b>STD</b>
60" Floating pin (In lieu of standard) .....	<b>\$885</b>
72" Floating pin (In lieu of standard) .....	<b>\$1,685</b>
72" Floating pin (SJ1256 THS carriage) (In lieu of standard) .....	<b>\$2,360</b>
48" Floating pin, side tilting (In lieu of standard) .....	<b>\$3,540</b>
60" Floating pin, side tilting (In lieu of standard) .....	<b>\$4,430</b>
72" Floating pin, side tilting (In lieu of standard) .....	<b>\$5,045</b>
72" Swing carriage (In lieu of standard) .....	<b>\$6,950</b>
For additional carriage add to in lieu of price .....	<b>\$2,460</b>

### Options‡

Closed cab .....	<b>\$6,260</b>
Air conditioning (Closed cab only) .....	<b>\$4,165</b>
Premium joystick.....	<b>\$3,605</b>
Four wheel fenders.....	<b>\$2,300</b>
Road lights .....	<b>\$1,150</b>
Work lights .....	<b>\$1,185</b>
Boom lights.....	<b>\$435</b>
Rotating beacon .....	<b>\$395</b>
Backup sensor .....	<b>\$2,450</b>
Backup sensor and camera .....	<b>\$5,755</b>
Cold weather package .....	<b>\$1,105</b>
<small>(Includes cold start engine oil, battery blanket &amp; hydraulic tank heater)</small>	
Arctic weather package .....	<b>\$2,585</b>
<small>(Includes cold start engine oil, battery blanket &amp; hydraulic tank heater, arctic hydraulic oil)</small>	
Service convenience package .....	<b>\$350</b>
<small>(Includes remote axle grease points &amp; clean drain oil valve)</small>	
Positive air shut-off valve .....	<b>\$4,485</b>
Pintle hitch.....	<b>\$660</b>
White noise alarm .....	<b>\$345</b>

### Optional Engine‡

107hp Deutz TCD3.6L .....	<b>\$9,100</b>
---------------------------	----------------

### Tire Options‡

Airless solid rubber 13 x 24 (In lieu of standard) .....	<b>\$5,320</b>
Non-marking airless solid rubber 13 x 24 (In lieu of standard) .....	<b>\$10,330</b>

‡ Standard lead times may be increased when optional equipment is added, consult factory

\*\* Capacities, and machine weights may differ when options are added



# TELEHANDLERS

LIST PRICING (USD) EFFECTIVE JANUARY 1ST, 2025

## SJ1256 THS..... \$237,180

- 12,000 lbs (5,443 kg) Maximum lift capacity
- 56'3" (17.1 m) Maximum lift height
- 6,000 lbs (2,722 kg) Capacity @ maximum lift height
- 7,000 lbs (3,175 kg) Capacity @ maximum lift height (on outriggers)
- 42'4" (12.90 m) Maximum forward reach
- 1,000 lbs (545 kg) Capacity @ maximum forward reach
- 3,500 lbs (1,588 kg) Capacity @ maximum forward reach (on outriggers)
- 2.25"x5"x48" Forks
- Tier 4 Final 107 hp/320 lb-ft Deutz TCD 3.6L engine
- Powershift, 3 speed transmission
- 3 Mode steering
- 48" Floating pin carriage with 48" Pallet forks
- Foam filled 14 x 24 rough terrain tires

### Standard Features

- Axle mount outriggers
- Auxiliary hydraulics
- Engine block heater
- Quick attach carriage mount
- Rear window with wiper
- Side window
- Suspension seat
- Single multifunction pilot operated joystick control
- In cab engine multifunction display
- Hydraulic test ports
- Lockable in cab storage box
- Steel engine cowling
- Steel component and access covers
- Telematics ready
- 2 Year Gold Leaf Warranty (5 year structural warranty)

### Forks‡

Pallet, 2.25"x5"x48", 12,000lbs capacity .....	<b>STD</b>
Pallet, 2.25"x5"x60", 12,000lbs capacity (In lieu of standard) .....	<b>\$745</b>
Pallet, 2.25"x5"x72", 12,000lbs capacity (In lieu of standard) .....	<b>\$1,225</b>
For additional set of forks add to in lieu of price.....	<b>\$1,975</b>

### Carriages‡

48" Floating pin carriage .....	<b>STD</b>
60" Floating pin (In lieu of standard).....	<b>\$1,215</b>
72" Floating pin (In lieu of standard).....	<b>\$1,985</b>
48" Floating pin, side tilting (In lieu of standard) .....	<b>\$3,640</b>
60" Floating pin, side tilting (In lieu of standard) .....	<b>\$4,565</b>
For additional carriage add to in lieu of price .....	<b>\$2,525</b>

### Options‡

Closed cab .....	<b>\$6,260</b>
Air conditioning (Closed cab only) .....	<b>\$4,165</b>
Premium joystick.....	<b>\$3,605</b>
Four wheel fenders.....	<b>\$2,300</b>
Road lights .....	<b>\$1,150</b>
Work lights .....	<b>\$1,185</b>
Boom lights.....	<b>\$435</b>
Rotating beacon .....	<b>\$395</b>
Backup sensor .....	<b>\$2,450</b>
Backup sensor and camera .....	<b>\$5,755</b>
Cold weather package .....	<b>\$1,105</b>
<small>(Includes cold start engine oil, battery blanket &amp; hydraulic tank heater)</small>	
Arctic weather package .....	<b>\$2,585</b>
<small>(Includes cold start engine oil, battery blanket &amp; hydraulic tank heater, arctic hydraulic oil)</small>	
Service convenience package .....	<b>\$350</b>
<small>(Includes remote axle grease points &amp; clean drain oil valve)</small>	
Positive air shut-off valve .....	<b>\$4,485</b>
Pintle hitch.....	<b>\$660</b>
White noise alarm .....	<b>\$345</b>

### Tire Options‡

Airless solid rubber 14 x 24 (In lieu of standard) .....	<b>\$8,180</b>
Non-marking airless solid rubber 14 x 24 (In lieu of standard) .....	<b>\$16,150</b>

‡ Standard lead times may be increased when optional equipment is added, consult factory

\*\* Capacities, and machine weights may differ when options are added





# TELEHANDLERS

LIST PRICING (USD) EFFECTIVE JANUARY 1ST, 2025

## ZB2044..... \$467,310

- 20,000 lbs (9,072 kg) Maximum lift capacity
- 44'10" (13.7 m) Maximum lift height
- 12,000 lbs (5,443 kg) Capacity @ maximum lift height
- 27'5" (8.4 m) Maximum forward reach
- 7,000 lbs (3,175 kg) Capacity @ maximum forward reach
- Cummins T4F QSB4.5C, turbocharged and charge-air-cooled diesel, 163hp @ 2500 rpm
- Powershift, 3 speed transmission
- 3 Mode steering
- 72" Floating pin carriage with 60" Pallet forks
- Foam filled 17.5 x 25 rough terrain tires

### Standard Features

- Outriggers
- Rear axle "Stable-Lock" cylinder with backup accumulator
- Standard quick attach carriage mount system
- Auxiliary hydraulic group for boom attachments
- Dual lift cylinders
- High pivot boom mount design
- ROPS/FOPS certified cab
- Rear window and side screen
- Lockable under cab storage compartment / step
- Adjustable suspension seat with seat belt
- Dual joystick pilot operated controls for boom and frame level functions
- Tilt adjustable joystick console
- Gauge instrumentation
- Electronic powerview engine monitor/gauge
- Lockable steel swing up engine doors
- Engine grid heater
- Dual element air cleaner with flow restriction indicator
- Dual batteries
- Independent front/rear brake systems
- Dual brake accumulators for dead engine braking
- Brake activated transmission disconnect
- 55 gallon (208 L) steel hydraulic tank
- 49 gallon (185 L) steel fuel tank
- Horn and backup alarm
- Mirrors, right and left side
- Remote grease fittings for axle trunnion mount lubrication
- Easy to remove steel component and access covers
- Operator/maintenance and parts manuals
- Telematics ready
- 2 Year Gold Leaf Warranty (5 year structural warranty)

### Additional Attachments‡

5 ft Jib boom (20,000 lbs capacity) .....	\$17,215
2.0 cu. yd. Light material handling bucket .....	\$9,300
Hydraulic winch (15,000 lbs capacity) .....	\$15,805
Pipe and pole clamp.....	\$55,200
Rotating pipe and pole manipulator .....	\$48,910
Bridge stripper .....	\$14,350

### Forks‡

Pallet, 2 3/4" x 6" x 60", 22,100lbs capacity.....	STD
Pallet, 2 3/4" x 6" x 72", 22,100lbs capacity (In lieu of standard) .....	\$520
Pallet, 2 3/4" x 6" x 96", 11,050lbs capacity (In lieu of standard) .....	\$2,850

For additional set of forks add to in lieu of price..... \$4,900

### Carriages‡

72" Floating pin carriage .....	STD
72" Dual hydraulic fork positioner (In lieu of standard) .....	\$7,150
84" Dual hydraulic fork positioner (In lieu of standard) .....	\$7,650
72" Side shift and dual hydraulic fork positioner (In lieu of standard) ..	\$16,150
84" Side shift and dual hydraulic fork positioner (In lieu of standard) ..	\$16,650

For additional carriage add to in lieu of price .....

### Options‡

Flashing beacon light.....	\$495
Lighting kit w/ guards – 2 front white / 2 rear red.....	\$1,150
Front and rear turn signals w/ flashers .....	\$830
Extra operating light with guard .....	\$350
Boom mounted operating lights .....	\$825
Front and rear fenders .....	\$4,120
Fully enclosed operator cab, .....	\$10,255
<small>(Includes sound insulation, heater, defroster, dome light, front and top windshield wiper)</small>	
Air conditioning – requires enclosed cab option.....	\$7,660
Mine package .....	\$22,275
<small>(Includes backup braking &amp; steering systems, drive shaft covers)</small>	
Backup sensor and camera .....	\$5,755
Positive air shut-off valve .....	\$4,485
Non destructive testing.....	\$1,595
White noise alarm .....	\$345

‡ Standard lead times may be increased when optional equipment is added, consult factory

\*\* Capacities, and machine weights may differ when options are added



# ELEVATE

## LIST PRICING (USD) EFFECTIVE JANUARY 1ST, 2025

### DIRECT

Connects rental fleets directly to your rental software (ERP) to make maintenance and billing processes more efficient and effective with live machine data.

- Transmits data every 15 minutes
- Provides full history of machine activity and engine status (data varies by machine)
- Data delivered by Trackunit IRIS API
- **Data access requires existing ERP software.** (Data-only package)
- 12, 36, 60 month packages
- Elevate hardware (IP 67 rated, Powered by Trackunit)

### ENGAGE

A full suite of tools to manage your connected fleet. In addition to direct data, Elevate Manager, GO, and Elevate Live deliver the benefits of connected machines to the service department and machine operators.

- **Elevate Manager and GO apps (powered by Trackunit)** Set alerts for machine operations or business rules to notify the right personnel in real time (SMS, Email)
- Generate up to the minute reports, giving you actionable insights to better your business
- Transmits data every 2/15 minutes or on I/O (delivers full machine history)
- Provides full history of machine activity and engine status (data set varies by machine)
- Includes **Direct** data to ERP delivered by Trackunit IRIS API (supported existing ERP software required)
- 12, 36, 60 month packages
- Elevate hardware (IP 67 rated, Powered by Trackunit)

### ENGAGE + ACCESS

Protect your assets and provide a safer worksite by adding access control to your fleet with Elevate Access. The Dual ID II keypad (powered by Trackunit) can limit access through PIN code, or RFID card to help make sure only properly trained personnel are operating your machines.

- Requires **Elevate Engage** Package and hardware
- Prevent machine ignition for non-credentialed personnel
- Limit machine access through PIN codes, or RFID cards (remotely programmable through Elevate Manager)
- Set auto expiring access codes to correspond to rental terms
- Dual ID II hardware is IP69 rated
- Works with IPAF PAL smart card for quick RFID access to machines

### 12 Month Plans

DIRECT .....	\$705
ENGAGE .....	\$790
ENGAGE + ACCESS .....	\$910

### 36 Month Plans

DIRECT .....	\$940
ENGAGE .....	\$1,110
ENGAGE + ACCESS .....	\$1,240

### 60 Month Plans

DIRECT .....	\$1,100
ENGAGE .....	\$1,375
ENGAGE + ACCESS .....	\$1,495

### BMS

BATTERY MANAGEMENT SYSTEM .....	\$250
---------------------------------	-------



# EXTENDED WARRANTY PLANS

LIST PRICING (USD) EFFECTIVE JANUARY 1ST, 2025

	2 years / 3000 hours	3 years / 4000 hours	5 years / 5000 hours
SJ12 E, SJ16 E, SJ20 E	n/c	\$932	\$2,796
SJ3213 micro, SJ3219 micro	n/c	\$952	\$2,855
SJ3215 E, SJ3219 E	n/c	\$952	\$2,855
SJ3220 E, SJ3226 E, SJ4726 E, SJ4732 E, SJ4740 E	n/c	\$1,384	\$4,152
SJ6826 RT, SJ6832 RT	n/c	\$3,018	\$9,054
SJ9233 RT, SJ9243 RT	n/c	\$5,002	\$15,025
SJ9253 RT, SJ9664 RT	n/c	\$6,149	\$18,447
SJ30 ARJE	n/c	\$4,455	\$13,365
SJ45 AJ+	n/c	\$5,697	\$17,091
SJ60 AJ+	n/c	\$8,316	\$24,948
SJ85 AJ	n/c	\$11,738	\$35,214
SJ40 T+, SJ45 T+	n/c	\$6,392	\$19,176
SJ61 T+, SJ66 T+	n/c	\$8,495	\$26,385
SJ82 T, SJ86 T	n/c	\$12,399	\$37,197
SJ519 TH	n/c	\$6,955	\$20,865
SJ643 TH	n/c	\$11,509	\$34,527
SJ843 TH	n/c	\$12,035	\$36,105
SJ1044 TH, SJ1056 TH	n/c	\$14,007	\$42,021
SJ1256 TH	n/c	\$16,727	\$50,181
ZB2044	n/c	\$27,135	\$81,405

**\*TERMS AND CONDITIONS:**

Extended warranty applies to new machines only and follows the standard warranty policy and procedure for the machine(s) purchased. Extended warranties must be purchased at point of machinery purchase, may not be applied to units that have entered service nor is it transferable. Extended Warranty Plans will follow the terms in the Warranty Terms and Policies.

**SKYJACK STANDARD WARRANTY POLICY**

SKYJACK INC., warrants that each new Mobile Elevating Work Platform (“MEWP”) will be free of defective parts and workmanship for two years (24 months or 3,000 hours, whichever comes first) from the date the product was invoiced to the purchaser or from the date the product was first put into service, whichever comes first. For the following 36 months, structural components found to be defective will be replaced or repaired at no charge. For further clarity MEWP Products include Scissor lifts and Boom Lifts.\*

SKYJACK INC., warrants that each new Telehandler manufactured by Skyjack Inc. will be free of defective parts and workmanship for two years (24 months or 3,000 hours, whichever comes first) from the date the product was invoiced to the purchaser or from the date the product was first put into service, whichever comes first. For the following 36 months structural components found to be defective will be replaced or repaired at no charge.\*

All warranty claims are subject to approval by Skyjack’s Service Department. Skyjack Inc. reserves a right to limit or adjust claims with regard to defective parts, labor or travel time based on usual and customary guidelines. Parts purchased from sources other than Skyjack will not be covered under this warranty. Misuse or improper operation, lack of normal maintenance and inspections as outlined in the Operating Manual, Parts Manual or Service Manual, alterations to original designs and/ or components or accidents will void all warranty. Batteries, wear items and engines are not covered by this warranty. Any claims, should refer to the manufactures warranties. Electrical failures due to loose wiring, corrosion & poor maintenance are not covered by this warranty.

SKYJACK INC. will repair or replace, at its option, the defective part or workmanship at its factory or authorized service center. The above warranty statement is exclusive and no other warranty whether written, oral or implied shall apply. Skyjack Inc. excludes any implied warranty of merchantability and fitness and accepts no liability for consequential damages or for others negligence.



# WARRANTY TERMS AND POLICIES

LIST PRICING (USD) EFFECTIVE JANUARY 1ST, 2025

Subject to the terms and conditions hereof, SKYJACK INC. ("Skyjack") warrants to the original buyer ("Buyer") that each new Mobile Elevating Work Platform ("MEWP") will be free of defective parts and workmanship under normal use and service for two years (24 months) from the date the product was invoiced to the Buyer or from the date the product was first put into service, whichever comes first. For the following 36 months, structural components found to be defective will be replaced or repaired at no charge. For further clarity, MEWP Products include only Vertical Mast Lifts, Scissor Lifts and Boom Lifts.

Subject to the terms and conditions hereof, SKYJACK INC., warrants to the Buyer that each new Telehandler manufactured by Skyjack Inc. will be free of defective parts and workmanship under normal use and service for (a) 3,000 hours of use; (b) two years (24 months) from the date the Telehandler was invoiced to the Buyer or (c) two years (24 months) from the date the Telehandler was first put into service, whichever comes first. For the following three years (36 months), structural components found to be defective will be replaced or repaired at no charge.

No claims under this warranty shall be valid unless written notice of the defect is provided to Skyjack or its authorized distributor within thirty (30) days after such defect is first discovered, and no longer than thirty (30) days after the end of the applicable warranty period. The failure to follow Skyjack's warranty claim procedures as described herein (and as may be modified by Skyjack from time-to-time) will invalidate the applicable warranty.

Skyjack's sole obligation to the Buyer is limited to the repair or replacement of any products or parts which Skyjack, in its sole discretion, determines to be defective in materials or workmanship, at Skyjack's option. Replacement products or parts may be new or factory approved reconditioned parts, at Skyjack's sole discretion. All repairs or replacement must be performed by technicians trained and qualified in accordance with ANSI standards, using only genuine Skyjack supplied parts, and must be made in accordance with the Warranty Claim Procedures provided herein. Any parts repaired or replaced under the warranty are warranted only for the balance of the warranty period on the part that was repaired or replaced.

Skyjack does not provide any warranty, and specifically disclaims any liability, relating to defective component parts or accessories that are not manufactured by Skyjack (for example, batteries, tires, engines, drive train components); however, Buyer may be entitled to the respective part's Original Equipment Manufacturer (OEM) pass-through warranty, if any (subject to any OEM terms and conditions).

This warranty does not apply to ordinary wear and tear. This warranty also does not apply to negligence; use beyond the products' rated capacity or other misuse or neglect; improper installation, storage or operation; lack of normal maintenance and/or inspections as outlined in Skyjack's Operator's Manual or Parts, Operation and Maintenance Manual, or any Skyjack technical bulletins ("Manuals"); service or repairs other than by technicians trained and qualified in accordance with ANSI standards, or using parts other than genuine Skyjack supplied parts (unless authorized in writing by Skyjack); electrical failures due to loose wiring or corrosion; alterations to original designs and/or components; accidents, floods, fires or other natural disasters or acts of God; the introduction of foreign materials to the products; or duties, taxes, environmental fees, including without limitations, disposal or handling of tires, batteries, and petrochemical items.

Skyjack's liability with respect to the products sold to Buyer shall be limited to this warranty, which constitutes Skyjack's entire and exclusive warranty as to the products and is the sole and exclusive remedy for defects in material and workmanship. Skyjack does not assume (and has not authorized any other person to assume on its behalf) any other warranty or liability in connection with any products covered by this warranty. In no event shall Skyjack's liability exceed the cost to repair or replace a defective product or part.

SKYJACK SHALL NOT BE SUBJECT TO ANY OTHER OBLIGATIONS OR LIABILITIES INCLUDING WITHOUT LIMITATION, CLAIMS FOR PERSONAL INJURY, DEATH, DISMEMBERMENT AND/OR PROPERTY DAMAGE (WHETHER ARISING OUT OF BREACH OF CONTRACT, WARRANTY, TORT (INCLUDING NEGLIGENCE AND STRICT LIABILITY)) OR UNDER OTHER THEORIES OF LAW OR EQUITY, OR WHERE THE THEORY OF LIABILITY IS BASED ON THE POSITION THAT THE PRODUCTS SHOULD HAVE EXCEEDED ANY STANDARDS IMPOSED BY APPLICABLE LAW, WITH RESPECT TO PRODUCTS SOLD BY SKYJACK, OR ANY UNDERTAKINGS, ACTS OR OMISSIONS RELATING THERETO. Without limiting the generality of the foregoing, Skyjack specifically disclaims any liability for property damage, penalties, special or punitive damages, damages for lost profits or revenues, down-time, lost good will, cost of capital, cost of substitute products or services, increased overhead, or for any other types of economic loss, or for claims of Buyer's customers or any third party for any such damages, costs or losses. SKYJACK SHALL NOT BE LIABLE FOR AND DISCLAIMS ALL CONSEQUENTIAL, INCIDENTAL, INDIRECT AND CONTINGENT DAMAGES WHATSOEVER.

This warranty shall be void if, upon the occurrence of any incident involving any products made by Skyjack and resulting in any personal injury or property damage, customer shall fail to notify Skyjack within 48 hours of such occurrence or permit Skyjack and its representatives to have immediate access to such products and all records of or within the control of customer relating to the products and occurrence. This warranty shall also be void if parts other than genuine Skyjack supplied parts (or parts authorized in writing by Skyjack) are used.

Buyer's rights hereunder are personal to the Buyer, and may not be transferred or assigned except with the prior written consent of Skyjack or by its authorized distributor as provided in a written distribution agreement between Skyjack and that distributor. Skyjack requires that all OEM's manufacture and supply components and parts to Skyjack in conformity with all ANSI, CSA and/or other relevant industry standards. Skyjack will not be liable under this warranty or otherwise where the defect is the result of an OEM's failure to meet this requirement.

EXCEPT FOR THE LIMITED WARRANTY PROVIDED HEREIN, SKYJACK EXPRESSLY DISCLAIMS ANY AND ALL OTHER WARRANTIES (EXPRESS OR IMPLIED) AS TO THE PRODUCTS FURNISHED HEREUNDER, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES AS TO MERCHANTABILITY IMPLIED) OR FITNESS FOR ANY PARTICULAR PURPOSE.



# ACCESSORYZERS™

Having equipment with features and functionality that allow you and your customers to do more is a vital part of the utilization equation. Skyjack offers a range of accessories to further expand a given product's ability to adapt and create a truly flexible rental choice.

To order, please contact our Parts department:  
 email: [parts@skyjack.com](mailto:parts@skyjack.com)  
 website: [skyjack.com/order-parts](http://skyjack.com/order-parts)  
 Tel: (630) 262-0005, Fax: (630) 262-0006  
 Toll Free: (800) 275-9522, Fax: (888) 782-4825

VERTICAL MAST LIFTS	SJ12 E	SJ16 E	SJ20 E
Light duty pipe rack	223586	223586	223586
Tool tray	223578		223578
Perimeter lights			
Florescent tube carrier	223575	223575	223575

DC SCISSOR LIFTS	SJ3213/19 micro	SJ3215/19	SJ3220/26	SJ4726/32	SJ4740
Light duty pipe rack		212585	212585	212585	212585
Heavy duty pipe rack		235056	235056	235056	235056
Board carrier		235059	235059	235059	235059
XStep / XStep micro	256785	240033			
Perimeter lights	248789	246383	246383	246383	246383
Platform mesh				256159	256159
Tool caddy		204334	204334	204334	204334

RT SCISSOR LIFTS	SJ6826/32 RT	SJ9233/43/53 RT	SJ9664 RT
Heavy duty pipe rack	196511	196511	196511
Tool caddy	204334	204334	204334
Material handling stand		195198	195198
Diesel scrubber for tier 4 final engine	139447	220424	220424

ARTICULATING BOOM LIFTS	SJ30 ARJE	SJ45 AJ+	SJ60 AJ+	SJ85 AJ
Pipe rack	192820	148559	162052	162052
Glazier kit		169156	162073	
Tool caddy	204334	204334	204334	204334
Half height mesh platform	223225			
Platform mesh		256507 / 256515 / 256516	256506 / 256515 / 256516	256506 / 256515 / 256516
Control box cover	216918	216918	216918	216918
Auxiliary top rail (30 x 72" platform only)		152575		
Auxiliary top rail (36 x 96" platform only)			162056	163408
Diesel scrubber for tier 4 final engine (T4 Deutz Engine)			148419	148419
Diesel scrubber for tier 4 final engine (D1305 Engine)		238740	238740	
Diesel scrubber for tier 4 final engine (2011 L03i Engine)		149115		



TELESCOPIC BOOM LIFTS	SJ40/45 T+	SJ61/66 T+	SJ82/86 T
Pipe rack	162052	162052	162052
Glazier kit	162073	162073	162073
Tool caddy	204334	204334	204334
Auxiliary top rail (36 x 96" platform only)	163409	163409	163409
Platform mesh	256506 / 256515 / 256516	256506 / 256515 / 256516	256506 / 256515 / 256516
Control box cover	216918	216918	216918
Diesel scrubber for tier 4 final engine	148419	148419	
Lifting lugs			168730

  

TELEHANDLERS	SJ519 TH	SJ643/843 TH	SJ1044/1056 TH	SJ1256 THS
Skid steer attachment	9-206089			
6' Truss Boom	9-206855			
66" Bucket	9-206125			
12' Truss boom		59199513	59199513	59199513
15' Truss boom				9-920337
1.75 Cubic yard bucket		9-927450	9-927450	9-927450
Partially enclosed cab	205894			
Fire extinguisher bracket	206459	9-204194	9-204194	9-204194

  

CARRIAGES				
48" Side Shift Carriage	9-205240			
53" Fork Positioner Carriage		9-206173	9-206173	9-206173
72" Side Tilting QA Carriage		13198742	13198742	13198742
48" Side Tilting QA Carriage	9-205239			
72" Swing Carriage		9-930011	9-930011	9-930011

  

FORKS				
Fully tapered, 4.5"x4"x48", 5,500lbs capacity	9-206869			
Fully tapered 1.75"x7"x48", 12,000lbs capacity		9-930274	9-930274	9-930274
Block 1 of 2"x1.5"x48", 5,500lbs capacity	9-206301			
Block 6 of 2"x1.5"x46", 9,000lbs capacity		9-922006	9-922006	9-922006